



2017 PRODUCT CATALOG

Cable Ties & Tubing

Line Code: AEL

NYLON CABLE TIES

	Natural SKU / Part#	UV Black SKU / Part#	Red SKU / Part#	Blue SKU / Part#	Length	Width (+/- 0.02")	Tensile Strength	PC
		5760037/ 83741			4"	0.14"	40 lbs	100
		6300030/ 83904	5760026/ 83900	5760025/ 83901	8"	0.18"	50 lbs	20
		6300820/ 83743			8"	0.18"	50 lbs	100
		22144333/ 83747			14"	100	0.18"	100

Operating Temperature -40°C to +85°C (-40°F to 185°F)

CABLE TIE ASSORTMENT PACKAGE

	SKU	Part#	Length	Width (+/- 0.02")	Tensile Strength	Natural PC	UV Black PC	Red PC	Blue PC	Yellow PC
	6300032	83748	4"	0.14"	40 lbs		100			
			8"	0.18"	50 lbs		150			
			11"	0.18"	50 lbs		50			
	10027407	83761	8"	0.18"	50 lbs	10	10			
	10027410	83762	12"	0.18"	50 lbs	10	10			
	25984901	83750	8"	0.18"	50 lbs		25			
			11"	0.18"	50 lbs		25			
	6300170	83754	4"	0.14"	40 lbs	10	10	10	10	10
			8"	0.18"	50 lbs	10	10	10	10	10
			11"	0.18"	50 lbs	10	10	10	10	10
	10027413	83763	6"	0.30"	120 lbs	50				
			8"	0.30"	120 lbs	40				
10"			0.30"	120 lbs	10					

Operating Temperature -40°C to +85°C (-40°F to 185°F)

CABLE TIE ASSORTMENT CANISTER PACKAGE

	SKU	Part#	Length	Width (+/- 0.02")	Tensile Strength	Natural PC	UV Black PC	Red PC	Blue PC	Yellow PC
	5760028	83756	4"	0.14"	40 lbs	100		25	25	50
			8"	0.18"	50 lbs	50	25	25		
* A roll of black Insulation tap (10.6' x 1") included										
	25984906	83771	4"	0.14"	40 lbs	150	150			
			8"	0.18"	50 lbs	150	150			
			11"	0.18"	50 lbs	50	50			

Operating Temperature -40°C to +85°C (-40°F to 185°F)

HEAVY DUTY #316 STAINLESS STEEL CABLE TIES

	SKU	Part#	Length	Width (+/- 0.02")	Tensile Strength	PC
	6760005	83916	11"	0.18"	100 lbs	10
Operating Temperature -60°C to +300°C (-76°F to 572°F)						




PVC HEAT SHRINK TUBING

	SKU	Part#	Length	Size	Gauge	Shrink Ratio	Color	Shrink Temperature
	6760003	85287	8'	9/32"	16 - 14	2 : 1	Blue	120° C (250° F) to 250° C (480° F)
	6760002	85286	8'	9/32"	20 - 18	2 : 1	Red	
	11333648	AC85265	8'	3/16"	16 - 14	2 : 1	Black	
	11333722	AC85266	8'	1/4"	20 - 18	2 : 1	Black	
Operating Temperature: -55° C (-67° F) to 125° C (257° F)								

PVC HEAT SHRINK TUBING ASSORTMENT PACKAGE


	SKU	Part#	Length	Size	Shrink Ratio	Color	PC	Shrink Temperature
	5760129	85611	6"	5/32"	2 : 1	Black	1	120° C (250° F) to 250° C (480° F)
			6"	7/32"	2 : 1	Black	1	
			6"	1/4"	2 : 1	Black	1	
			6"	9/32"	2 : 1	Black	1	
			6"	12/32"	2 : 1	Black	1	
	6300812	85686	5"	1/8"	2 : 1	Red	3	
			5"	7/32"	2 : 1	Blue	2	
			5"	9/32"	2 : 1	Yellow	1	
			5"	17/32"	2 : 1	Blue	1	
Operating Temperature: -55° C (-67° F) to 125° C (257° F)								

WIRE CONDUITS

	SKU	Part#	Length	Size	Inner Diameter	Outer Diameter	Color
	16320044	86650	10'	3/8"	0.56"	0.73"	Red
	16320052	86651	10'	3/8"	0.56"	0.73"	Blue
	89010784	85636	3'	3/4"	0.91"	1.12"	Black

Operating Temperature: -30° C (-22° F) to 100° C (212° F)

SPIRAL TUBING

	SKU	Part#	Length	Size	Inner Diameter	Outer Diameter	Screw	Wrapping Range	Color
	5760131	86135	10'	3/8"	0.31"	0.39"	0.31"- 0.39"	0.29" to 1.18"	Black

Operating Temperature -40°C to +100°C (-40°F to 212°F)