


FLEET ESSENTIALS

QUICK REFERENCE GUIDE



**WE MAKE PRODUCTS THAT
MAKE A DIFFERENCE™**

12070 Burke Street
Santa Fe Springs, CA 90670
800-423-4512 Fax: 800-597-7757
B-FE-0509

PHILLIPS

www.phillipsind.com
800-423-4512

ABS LECTRACOIL™



QCP™
option available



16-125
Replacement

1/8, 2/10 & 4/12 ga. ABS Trailers

Part No.	Description
30-9620	15', with PERMAPLUGS™
30-9621	15', with zinc die-cast plugs
30-9624	15', with QCP™ (Quick-Connect Plugs)
30-9920	15', 48" lead with PERMAPLUGS™
30-9921	15', 48" lead with zinc die-cast plugs
30-9924	15', 48" lead with QCP™ (Quick-Connect Plugs)

- Replaceable cartridge for quick & easy repair
- Best for ABS applications
- Plug is sealed for corrosion protection
- Temperature rating -82°F to 195°F (-63°C to 91°C)

For a complete listing of electrical assemblies, see our full line catalog.

ABS PERMACOIL™

QCP™
option available



NEW

NEW

NEW

1/8, 2/10 & 4/12 ga. ABS Trailers

Part No.	Description
30-4324	12', with QCP™ (Quick-Connect Plugs)
30-4620	15', with PERMAPLUGS™
30-4621	15', with zinc die-cast plugs
30-4624	15', with QCP™ (Quick-Connect Plugs)
30-4924	15', 48" lead with QCP™ (Quick-Connect Plugs)

- Good for ABS applications
- Temperature rating -87°F to 150°F (-66°C to 66°C)

For a complete listing of electrical assemblies, see our full line catalog.

PERMACOIL™

QCP™
option available



NEW

NEW

1/12 & 6/14 ga. NON-ABS Trailers

Part No.	Description
24-4324	12', with QCP™ (Quick-Connect Plugs)
24-4621	15', with zinc die-cast plugs
24-4624	15', with QCP™ (Quick-Connect Plugs)

- For standard 7-way applications, NON-ABS equipped trailers
- Temperature rating -87°F to 150°F (-66°C to 66°C)

For a complete listing of electrical assemblies, see our full line catalog.

ABS LECTRAFLEX™

QCP™
option available



NEW

NEW

1/8, 2/10 & 4/12 ga. ABS Trailers

Part No.	Description
30-2050	12', with PERMAPLUGS™
30-2071	15', with zinc die-cast plugs
30-2091	20', with zinc die-cast plugs
30-2094	20', with QCP™ (Quick-Connect Plugs)

- For ABS applications

For a complete listing of electrical assemblies, see our full line catalog.

Liftgate Assemblies



Two 4 ga. Fine-Stranded Copper

Part No.	Description
23-2326	Dual pole - 12', 1 ground, 1 hot, 100 amp capacity
23-2626	Dual pole - 15', 1 ground, 1 hot, 100 amp capacity
23-4325	Single pole - 12', 1 hot, 100 amp capacity
23-4625	Single pole - 15', 1 hot, 100 amp capacity

- Excellent ratings for recoil memory, chemical resistance & abrasion resistance
- Temperature rating -82°F to 195°F (-63°C to 91°C)
- Zinc die-cast housing, reinforced for durability

For a complete listing of electrical assemblies, see our full line catalog.

Electrical & Air Hose Assembly

Part No.	Description
22-2171	15' assembly, NON-ABS with zinc die-cast plugs
30-2171	15' assembly, ABS with zinc die-cast plugs
30-2174	15' assembly, ABS with QCP™ (Quick-Connect Plugs)
30-2191	20' assembly, ABS with zinc die-cast plugs
30-2194	20' assembly, ABS with QCP™ (Quick-Connect Plugs)

- Spiral-wrapped for an organized, clean look
- Large grips for great coupling/uncoupling leverage and strain relief
- Swivel end brass fitting on tractor side of air hoses
- Outstanding kink and abrasion resistance
- Includes hanging clip for easy installation
- Available with Phillips Quick-Connect Plug (QCP™) assembly for fast plug repair

For a complete listing of electrical plugs, see our full line catalog.



Part No.	Description
16-730	PERMAPLUG™

- Unbreakable DuPont Super-Tuff Nylon® housing
- 360 degree cable compression fitting holds cable tight
- Housing resists magnesium chloride, salt, oil, grease and fuels
- ABS insert protects housing from impacts
- Easy replacement insert

For a complete listing of electrical plugs, see our full line catalog.

PERMAPLUG™



Part No.	Description
15-730	Industry-standard plug with cable guard

- Zinc die-cast housing, reinforced for durability
- 15-731 replacement cable guard
- Large finger grips to accommodate gloves
- Easy replacement insert

For a complete listing of electrical plugs, see our full line catalog.

Zinc Die-Cast Plug



Part No.	Description
15-335	Single pole plug
15-336	Dual pole plug

- Industry-standard plug
- Zinc die-cast housing, reinforced for durability

For a complete listing of electrical plugs, see our full line catalog.

Liftgate Plugs



Part No.	Description
16-720	2-hole, wire insertion
16-724	Replacement socket — 2-hole, bullet termination, recommended for use with Phillips QCS2®

- For protection against corrosion, use socket boot P/N 15-740
- Inner cavity sealed to prevent corrosion from passing to wire harness
- Extended front barrel for additional cable support

For a complete listing of electrical sockets, see our full line catalog.

STA-DRY® Wire Insertion Socket



7-Way Socket



Part No.	Description
----------	-------------

15-720	2-hole, wire insertion, split pin
---------------	-----------------------------------

- Zinc die-cast housing for durability
- Elongated holes for mounting adaptability
- Stainless steel hinge pin and spring for long life
- Full-opening lid
- Angled 5° for water drainage
- Reduce exposure to contaminants & moisture, use socket boot P/N 15-740

For a complete listing of electrical sockets, see our full line catalog.

7-Way Socketbreakers



Quick-change
circuit breakers



Part No.	Description
----------	-------------

15-760	Without circuit breakers, split pin
---------------	-------------------------------------

15-761	With 15 amp circuit breakers, split pin
---------------	---

15-762	With 20 amp circuit breakers, split pin
---------------	---

15-763	With 30 amp circuit breakers, split pin
---------------	---

- Stainless steel hinge pin and spring for long life
- Full-opening lid
- Includes neoprene closed cell sponge mounting gaskets
- Circuit breaker can be changed in 30 seconds

For a complete listing of socketbreakers, see our full line catalog.

Liftgate Sockets



Part No.	Description
----------	-------------

15-320	Single pole socket, for use with 4 gauge, 5/16" lug
---------------	---

15-326	Dual pole socket
---------------	------------------

- 100 amp capacity
- Zinc die-cast housing for durability
- Solid brass pins
- Elongated holes for mounting adaptability
- Stainless steel hinge pin and spring for long life
- 5/16" stud size for lugs

For a complete listing of electrical sockets, see our full line catalog.

STOW-A-WAY™



Part No.	Description
----------	-------------

15-041	1 plug, 2 gladhand holder
---------------	---------------------------

15-042	2 plug, 2 gladhand holder
---------------	---------------------------

- 32% of truckers Workmen's Comp claims are from accidents occurring behind the cab, according to leading insurance carriers
- Offers safe, easy storage for coiled electrical cable and air lines when not in use
- Corrosion resistant and extremely durable

For a complete listing of cable support products, see our full line catalog.

Pogo Sticks



Part No.	Description
----------	-------------

17-0400	40" chrome
----------------	------------

17-0401	40" gold chromate
----------------	-------------------


- Designed for use with heavier ABS cables
- Can accept STOW-A-WAY™ (15-041, 15-042), needs 17-039 mounting kit
- Can accept gladhand holder (15-039)
- Aircraft-quality 7/16" mounting bolt
- Includes 3-hose holder
- Extra heavy-duty 8" coated spring for corrosion resistance

For a complete listing of cable support products, see our full line catalog.

Part No.	Description	Qty.
17-148-25	Tracker bar spring kit, 20" spring	25
17-152	QWIK-SNAP™ 2-hose holder	1
17-153	QWIK-SNAP™ 3-hose holder	1
17-154	QWIK-SNAP™ 4-hose holder	1
17-160	Snap-on clip	1

- Change your tracker bar spring in seconds!
- Kit includes snap-on clip, sleeve, 3-hose holder & spring(s)


For a complete listing of cable support products, see our full line catalog.



Part No.	Description
11-5120	12' pair (red & blue)
11-5150	15' pair (red & blue)
11-5400	15' pair (red & blue), with 40" lead

- REMAINS FLEXIBLE AT -85°F (-65°C)! FOR EXTREME WEATHER CONDITIONS
- Excellent recoil memory, chemical & abrasion resistance
- POWER GRIP™ gladhand extension provides superior coupling/uncoupling leverage
- Large coil diameter prevents kinking and provides greater recoil


For a complete listing of air assemblies & connectors, see our full line catalog.



Part No.	Description
11-3120	12' pair (red & blue)
11-3150	15' pair (red & blue)
11-3400	15' pair (red & blue), with 40" lead

- Perfect for frequent coupling/uncoupling
- Extra-long brass handle adds cold weather coupling/uncoupling leverage
- Extra-long plated spring adds life to nylon tubing ends
- Vertical at the tractor, angled at the trailer end to prevent hose kinking
- Includes thread seal for secure connection to gladhand & chassis

For a complete listing of air assemblies, see our full line catalog.



Part No.	Description
11-312	12' pair (red & blue)
11-315	15' pair (red & blue)
11-340	15' pair (red & blue), with 40" lead

- Industry-standard nylon tubing
- Vertical at the tractor end, angled at the trailer end to prevent hose kinking
- Plated steel spring for cable support

For a complete listing of air assemblies & connectors, see our full line catalog.

Heavy-Duty Coiled Air



Part No.	Description
11-8110	12', with red grip, emergency
11-8111	12', with blue grip, service
11-8112	12' set, with red/blue grips
11-8115	15' set, with red/blue grips
11-8117	15', with red grip, emergency
11-8118	15', with blue grip, service
11-8119	15', with black grip, universal
11-8120	20' set, with red/blue grips
11-8121	20', with red grip, emergency
11-8122	20', with blue grip, service
11-8123	20', with black grip, universal


- Tractor end includes swivel fitting for easy installation and spring guard for strain relief
- Large grips for easy coupling/uncoupling and hose support
- Provides excellent abrasion resistance and resists cracking, kinking and weathering

For a complete listing of air assemblies & connectors, see our full line catalog.

Rubber Air Lines



Straight & Angle Mount Gladhands



Part No.	Description
12-006	Service, blue
12-008	Emergency, red
12-010	Universal
12-136	Service, blue, bottom port, angled
12-138	Emergency red, bottom port, angled

- Wrap-around connector plate provides additional strength
- Powder-coated connector plate for corrosion resistance
- Zinc-coated detent plates
- Keyed for positive connection
- E-coated screws for corrosion protection
- For use on air coil, tractor & trailer
- 1/2" pipe port

For a complete listing of gladhands, see our full line catalog.

QWIK-E® Gladhands



Part No.	Description
12-206	1/2" female pipe thread without filter screen
12-236	3/8" female pipe thread bottom port, angled

- Eliminates trailer tire flat spots
- Trailer brakes are released up to 50% faster
- Quick-release valve and gladhand combined
- Anodized housing for corrosion protection
- For use with ABS and NON-ABS brake systems
- By reducing brake lining and drum wear, thousands of dollars are saved over the life of the trailer

For a complete listing of gladhands, see our full line catalog.

Coiled Air Grips



Part No.	Description
12-600	Pair, (red & blue), clamshell

- Provides extra leverage for coupling/uncoupling gladhands
- One-piece body for easy installation
- Durable and strong; made from solid aluminum
- Corrosion-resistant anodized color coating
- Easy installation - Installs between aircoil and gladhand

For a complete listing of gladhand accessories, see our full line catalog.

Battery Cable




Part No.	Gauge	Pkg.	Length	Stranding	Jacket	O.D.
3-503	4	Box	25'	133 x 26	Red	0.405
3-504	4	Box	25'	133 x 26	Black	0.405
3-511	2/0	Box	25'	259 x 23	Red	0.640
3-512	2/0	Box	25'	259 x 23	Black	0.640

- Rope-style stranding for flexibility
- Easy to strip
- Superior abrasion resistance
- Temperature range -40°F to 150°F (-40°C to 66°C)
- Meets SAE J1127 SGT specifications

For a complete listing of battery cable, see our full line catalog.

CLEAR-VU™ High-Performance Battery Cable



Part No.	Gauge	Pkg.	Length	Stranding	Jacket	O.D.
3-532	2/0	Box	25'	259 x 23	CLEAR-VU™, clear	0.595
3-565	2/0	Box	25'	259 x 23	CLEAR-VU™, red	0.595
3-566	2/0	Box	25'	259 x 23	CLEAR-VU™, smoke	0.595

- Translucent jacketing provides early corrosion detection
- Prevents premature battery replacement
- Rope-style stranding for flexibility
- Superior abrasion resistance
- Temperature range -40°F to 150°F (-40°C to 66°C)

For a complete listing of battery cable, see our full line catalog.

7 CONDUCTOR 6/12, 1/10 GA. .640 O.D. <i>Black - Brown - Blue - Green - Red - White - Yellow</i>			
Part No.	Cable Type	Length	Package
3-221	DURAFLEX™	50'	Box
3-222	DURAFLEX™	100'	Box
3-223	DURAFLEX™	250'	Spool
3-224	DURAFLEX™	500'	Spool

7 CONDUCTOR 6/14, 1/12 GA. .570 O.D. <i>Black - Brown - Blue - Green - Red - White - Yellow</i>			
Part No.	Cable Type	Length	Package
3-241	DURAFLEX™	50'	Box
3-242	DURAFLEX™	100'	Box
3-243	DURAFLEX™	250'	Spool
3-244	DURAFLEX™	500'	Spool
3-245	DURAFLEX™	1000'	Spool

- Flexible trailer cable suited best for trailer re-wiring
- Black jacket color
- Temperature range - 40°F to 150°F (-40°C to 66°C)

For a complete listing of bulk cable, see our full line catalog.

DURAFLEX™ Trailer Cable



Color		100 ft Spool	1000 ft Spool
14 Gauge	Purple	2-120	—
	Black	2-121	2-121-1000
	Blue	2-122	2-122-1000
	Brown	2-123	2-123-1000
	Green	2-124	2-124-1000
	Red	2-125	2-125-1000
	White	2-126	2-126-1000
	Yellow	2-127	2-127-1000
	Orange	2-128	2-128-1000
	Pink	2-129	—
	Red/Black	2-1215	—

For a complete listing of primary wire, see our full line catalog.

Primary Wire



Gauge	Description	Positive	Negative
2/0	Straight clamp	8-1160	8-1161
2/0	Left elbow clamp	8-1260	8-1261
2/0	Right elbow clamp	8-1360	8-1361
2/0	Flag	8-1460	8-1461

GROUP 31

Gauge	Description	Single	Dual
2/0	Rotating, Group 31	8-1763	8-1863
2/0	Non-rotating, Group 31	8-4763	8-4863

- Copper battery connectors tin plated for added conductivity and corrosion resistance
- Ideal for crimping or soldering
- Exceeds SAE conductivity standard J163 and J1811

For a complete listing of battery terminals & accessories, see our full line catalog.

Crimpable Battery Terminals



Copper Lugs



GA	#10	1/4"	5/16"	3/8"	1/2"
8	8-2100	8-2101	8-2102	8-2103	8-2105
6	8-2110	8-2111	8-2112	8-2113	8-2115
4	—	8-2121	8-2122	8-2123	8-2125
2	—	8-2131	8-2132	8-2133	8-2135
1	—	8-2141	8-2142	8-2143	8-2145
1/0	—	—	8-2152	8-2153	8-2155
2/0	—	—	8-2162	8-2163	8-2165
3/0	—	—	8-2172	8-2173	8-2175
4/0	—	—	—	8-2183	8-2185

For a complete listing of copper battery lugs, see our full line catalog.

STA-DRY® Heat Shrink Connectors



Multiple Wire Connector



Step-down Connector



Butt Connector

Part No.	Description
1-1724	16-14 ga., multiple wire connector, 10/bag
1-1728	20-18 ga. to 16-14 ga., step-down connector, 10/bag
1-1962	16-14 ga., butt connectors, 25/bag

For a complete listing of heat shrink connectors, see our full line catalog.

STA-DRY® Flexible Dual Wall Heat Shrink Tubing



Part No.	Expanded ID	After Recovery	Wire Gauge	Color	Pieces & Bag
6-305	0.750"	0.250"	1-2/0	Black	6-6" Pcs.
6-306	0.750"	0.250"	1-2/0	Red	6-6" Pcs.

For a complete listing of shrink tubing, see our full line catalog.

Torches



Part No.	Description
4-054	Mini-jet torch, blister pack
4-057	Professional torch, box

- Waterproof ignition system
- Refillable tank
- Adjustable gas flow

For a complete listing of heat torches, see our full line catalog.



Part No.	Description
60-2215	LED dome lamp, individual retail boxes
60-2216	LED dome lamp, 6 pack bulk

- 2X more light output than competitive lamps!
- Draws only 1.8 amps at 12V DC
- Universal mounting holes
- 1" thin (.73" recessed) design can fit just about any application
- UNBREAKABLE polycarbonate lens and housing
- Designed for extreme temperatures : -40°F (-40°C) to +140°F (60°C)
- 175° light spread offers more lit area inside the trailer

For a complete listing of PERMALITE™, see our full line catalog.

Document Holder



Part No.	Description	Qty.
16-800	Document holder	1
16-800-25	Document holder, bulk pack	25

- Water proof – Documents remain dry in extreme weather
- Twist-on lens with large grips – Easy to use with gloves
- Stainless steel hardware – Keeps documents rust free
- Mounts with most competitive document holders
- Large interior for multiple documents