

TIRE SERVICE INFLATORS

- **ACCURATE:** Measures in PSI (0-255), kPa (0-1800), kg/cm² (0-18), and Bar (0-18). Meets ANSI/ASME B40.1 standards.
- **GAUGE SWIVELS:** Reads at any angle, lays flat in your toolbox. Gauge protected by rubber boot.
- **BACKLIT DISPLAY:** Auto-on when tire pressure is detected; Auto-off after inactivity to save battery.
- **EASY HANDLING:** Durable/ergonomic grip. Quick fine tuning in case you exceed the target pressure
- **6" STRAIGHT FOOT CHUCK:** Full swivel + hose w/threaded lock-on design, enabling hands-free inflation.

Milton Industries Pro Digital Tire Inflator/Pressure Pistol Grip Gauge - Straight Foot Chuck w/Lock-On Threads, 15" Hose MIL S-577D



- **ACCURATE:** Measures in PSI (0-255), kPa (0-1800), kg/cm² (0-18), and Bar (0-18). Meets ANSI/ASME B40.1 standards.
- **GAUGE SWIVELS:** Reads at any angle, lays flat in your toolbox. Gauge protected by rubber boot.
- **BACKLIT DISPLAY:** Auto-on when tire pressure is detected; Auto-off after inactivity to save battery.
- **EASY HANDLING:** Durable/ergonomic grip. Quick fine tuning in case you exceed the target pressure.
- **6" DUAL FOOT CHUCK:** With 360 degree swivel and 15" hose easily reaches into Dually tires.

Milton Industries Pro Digital Tire Inflator/Pressure Pistol Grip Gauge - Classic Dual Head Chuck, 15" Hose MIL S-576D



- Digital Easy-to-Read Backlit LCD Screen with ± 1 PSI Accuracy & Auto Turn off
- Protective Rubber Boot
- Measure Range: 0-100 PSI, 0-7 Bar, 0-7 kg/cm², 0-700 kPa
- Full Pull to Inflate & Half Pull to Deflate
- Integrated Hang Loop for easy storage

Milton Industries Pistol Grip Digital Tire Inflator Gauge MIL EX0500D



- Full swivel chuck
- Includes a 15 inch hose
- Pressure range of 10 to 60 pounds per square inch in 2 pound increments

Milton Industries Dual Head Chuck Inflator Gauge MIL S506



- Full swivel chuck
- Offers lock on threads for convenience
- Equipped with magnifying lens for full view of scale
- Range of 10-160 pounds per square inch or 80-840 kilopascal
- 15 Inch hose length

Milton Industries Straight Foot Dual Head Chuck Inflator Gauge MIL S516



- 1/4" national pipe thread
- Dual chuck head for truck tires
- Includes a jumbo white nylon indicator bar
- Hose whips are interchangeable with any Milton bayonet gauge

Milton Industries Dual Head Chuck Bayonet Inflator Gauge MIL S522



- Includes a 5 foot hose
- Pressure range of 10 to 160 pounds per square inch
- Thread size 3/8-24
- Includes deflator valve
- Full swivel chuck head

Milton Industries Dual Head Straight Chuck Inflator Gauge MIL 501



- 1/4" female national pipe thread
- Designed and manufactured to exacting standards
- Maximum air pressure of 150 pounds per square inch

Milton Industries 1/4" Straight Foot Dual Head Air Chuck MIL S693



- 1/4" female national pipe threads
- Both ends lock on valve core threads
- Maximum pressure of 150 pounds per square inch

Milton Industries 1/4" FNPT Extended Reach Dual Head Air Chuck MIL S-693-12



- 1/4" female national barb
- Maximum air pressure of 150 pounds per square inch
- Not for use with inflator gauge

Milton Industries 1/4" FNPT Single Head Air Chuck with Grip MIL S698



- Designed and manufactured to exacting standards
- Closed/sealing type chuck
- 1/4" Female national pipe thread
- 1/4" hose inside diameter

Milton Industries 1/4" Single Head Air Chuck MIL S699



- 1/4" female national pipe thread
- Maximum air pressure of 150 pounds per square inch
- 1/4" hose inside diameter
- Not for use on Milton inflator gauges
- Designed and manufactured to exacting standards

Milton Industries 1/4" ID Euro Style Hose Barb Air Chuck MIL S697



TIRE SERVICE TIRE GAUGES

- Measures pressure from 2-99.5 pounds per square inch or 15-700 kilopascal
- Features an automatic shut off
- Included one CR 2032 3V battery

Milton Industries Single Head Chuck Digital Tire Gauge MIL S-99900



- Single head chuck
- Pressure range of 5-50 pounds per square inch or 40-350 kilopascal
- Includes deflator valve

Milton Industries Passenger Car Tire Gauge MIL S921



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Scales range from 20-120 PSI and 120-820 kPa
- Manual Pencil Tire gauge with a single head chuck and a deflator valve
- Pocket Clip helps keep the gauge secure to you or any tool bag
- USA precision machined components
- 4-Sided bar with psi and kPa scale

Milton Industries Pencil Tire Gauge MIL S925



- Perfect for ATVs, golf carts and air springs
- Made with machine parts unlike the competition
- Includes inflator gauge
- Range of 2-20 psi

Milton Industries Low Pressure Tire Gauge MIL S917



- Made from machined parts, unlike the competition
- Built in tire thread depth gauge in 1/16" increments
- Built in deflator valve
- Great for higher pressure automobile tires
- Pressure range of 10 - 70 pounds per square inch or 60 - 500 kilopascal

Milton Industries Pencil Tire Gauge with Depth Gauge MIL S920



- For use on air/water filled tires
- Calibrated 2 sides - 5 to 50 PSI in 1 lb increments 2 sides - kilo Pascals (kPa) 40 to 350 in 10 kPa increments

Milton Industries Tractor Tire Gauge MIL S928



- Tire gauges provide accurate, long life with trouble free performance
- Working pressure range of 20 to 120 pounds per square inch in 2 pound increments
- Reads in both kilopascal and pounds per square inch

Milton Industries Dual Head Truck Tire Gauge MIL S927



- Calibrated 2 sides - 10 to 160 lbs. in 2 lb increments 2 sides - 80 to 1100 kilo Pascals in 20 kPa Units Red Marker

Milton Industries Extension Service Gauge (D. H. Chuck) MIL S976



- Precision engineered to give you master gauge accuracy in a long life service gauge.
- Calibrated 2 sides - 10 to 160 lbs. in 2 lb. increments 2 sides - 80 to 1100 kilo Pascals in 20 kPa units Red Marker
- Includes dual head chuck and easy to read nylon indicator bar

Milton Industries Extension Service Straight Gauge (10 to 160 lbs) MIL S986



- Durable hot stamped, not pad printed indicator bar
- Solid brass tube with nickel plating
- 100% calibrated
- Hang up loop
- Maximum 160 pounds per square inch or 1100 kilopascal

Milton Industries Dual Head Large Bore Chuck Service Gauge MIL S-982



- Maximum 60 pounds per square inch
- Single head chuck
- Includes deflator valve

Milton Industries Single Head Dial Gauge MIL S932



- 1/4" national pipe thread
- Pressure range of 0 to 160 pounds per square inch
- Temperature range of -13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/4" NPT Pressure Gauge MIL 1194



- 1/4" national pipe thread
- Pressure range of 0 to 300 pounds per square inch
- Temperature range of -13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/4" NPT High Pressure Gauge MIL 1195



- 1/4" national pipe thread
- Pressure range of 0 to 160 pounds per square inch
- Temperature range of -13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/4" NPT Mini High Pressure Gauge MIL 1191



- 1/8" male national pipe thread
- Pressure range of 0 to 160 pounds per square inch
- Temperature range of -13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/8" NPT Mini High Pressure Gauge MIL 1189



TIRE SERVICE TIRE HARDWARE TOOLS

- Works with both standard and large bore valves
- Overall Length of 5"
- 3" molded handle

Milton Industries Combination Valve Core Tool MIL S444



- For the installation or removing of snap-in type tubeless tire valves

Milton Industries Valve Insertion and Removal Tool MIL S449



- Calibration range of 0 to 1" in 1/32" markings
- Round aluminum indicator bar
- Includes a pocket clip

Milton Industries Tire Tread Depth Gauge MIL S448



- Convenience of four tools in one
- Rethread inside and outside of valve stems
- Insert or remove valve cores
- Tap size of .2108-36

Milton Industries 4 in 1 Valve Repair Tool MIL S445



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

TIRE SERVICE

AIR & WATER VALVE

- Connects 3/4" garden hose to tire valves to fill tires with liquid
- Fits all tubes and tubeless valves
- Complete with 2 adapters - one standard bore and one large bore

Milton Industries 3/4" GHT Air and Water Adapter Valve MIL S466



TIRE SERVICE

TIRE BORE ADAPTER

- Tire and rim type TR-AD1
- 0.305-32 thread size
- Easily threads onto existing tire valves

Milton Industries Large Bore Adapter MIL 1460



TIRE SERVICE

TIRE CHUCKS

- 1/4" female national pipe thread
- Closed/sealing type chucks
- Maximum inlet pressure of 150 pounds per square inch
- Not for use on Milton inflator gauges

Milton Industries 1/4" FNPT Kwik Grip Safety Chuck MIL S696



- 1/4" female national pipe thread
- Use for off road trucks and heavy duty equipment
- 5 1/8" handle length for easy use

Milton Industries 1/4" FNPT Long Handled Lock On Air Chuck MIL 1471



- 1/4" female national pipe thread
- Maximum of 150 pounds per square inch
- Locks onto tire valve threads

Milton Industries 1/4" FNPT Kwik Grip Safety Large Bore Air Chuck MIL 1496



TIRE SERVICE

TIRE CAPS

- Standard hex head valve cap
- Chrome plated brass
- Simply thread valve cap onto existing valve core

Milton Industries High Performance Hex Head Valve Cap MIL 435

Milton Industries High Performance Hex Head Valve Cap MIL S435

Image Shown: 435



- Replaces caps on vehicles, bikes and lawn equipment
- Plastic dome type
- Tire and rim association type VC8

Milton Industries TR VC 8 Dome Type Valve Cap MIL 439




TIRE SERVICE

TIRE VALVE EXTENSIONS

- Maximum of 150 pounds per square inch
- Standard bore

Milton Industries 8 1/4" Valve Stem Extension MIL S400-6



- 5 1/2" total effective length
- High heat cap with a thread size of .305-37
- For use with trucks or buses

Milton Industries 5 1/2" Truck Valve Extension MIL 440-5



- 4 1/8" total effective length
- High heat cap with a thread size of .305-37
- For use with trucks or buses

Milton Industries 4 1/8" Truck Valve Extension MIL 440-4



TIRE SERVICE

TIRE VALVES

- Operating pressure range of 0 to 200 pounds per square inch
- Operating temperature range of -40 degrees Fahrenheit to 302 degrees Fahrenheit
- Meets tire and rim specification TR C1

Milton Industries TR C1 Tire Valve Core MIL 404



- Operating pressure range of 0 to 200 pounds per square inch
- Operating temperature range of -40 degrees Fahrenheit to 302 degrees Fahrenheit
- Meets tire and rim specification C1

Milton Industries TR C1 Tire Valve Core MIL 404-100



- Operating pressure range of 0 to 200 pounds per square inch
- Operating temperature range of -40 degrees Fahrenheit to 302 degrees Fahrenheit
- Meets tire and rim specification TR C1

Milton Industries TR C1 Tire Valve Core MIL S404



- Replacement part
- Complete with valve core and cap for use with tractor valve
- Includes valve core and valve cap

Milton Industries TR CH3 Valve Core Housing MIL S464



- Tire and rim type 416
- Thread size of .453 and 5/8"
- For tire pressure over 45 pounds per square inch

Milton Industries TR 416 Clamp In Tubeless Tire Valve MIL 470



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Tire and rim type TR 510
- 5 1/2" overall length
- Includes Milton nickel plated dome type valve cap #437
- Includes a Milton nickel plated dome type valve cap #437

Milton Industries TR 510 Tubeless Truck Tire Valve MIL 492



- 2 1/2" total effective length
- Maximum pressure of 90 pounds per square inch
- Tire and rim type 618A

Milton Industries 2 1/2" TR 618A Tubeless Air Liquid Valve MIL 469



- 1 1/4" effective length
- Fits .453 rim holes
- Tire and rim type 413

Milton Industries 1 1/4" Chrome Tubeless Tire Valve MIL S413-1



- 1 1/4" total effective length
- Tire and rim type TR 600
- Fits rim hole diameter of .453

Milton Industries 1 1/4" High Pressure Tubeless Tire Valve MIL 493-50



- 2" effective length
- Made of ozone resistant rubber
- Maximum cold inflation pressure of 60 pounds per square inch
- Tire and rim type 418

Milton Industries 2" Tubeless Tire Valve MIL 418-50



- 1 1/2" effective length
- Made of ozone resistant rubber
- Maximum cold inflation pressure may not exceed 60 pounds per square inch
- Tire and rim type 414

Milton Industries 1 1/2" Tubeless Tire Valve MIL 414-50



- 1 1/4" effective length
- Fits .453 rim holes
- Tire and rim type 413

Milton Industries 1 1/4" Tubeless Tire Valve MIL 413-50

Milton Industries 1 1/4" Tubeless Tire Valve MIL 413-10

Milton Industries 1 1/4" Tubeless Tire Valve MIL S413



- 1 1/4" effective length
- Made of ozone resistant rubber
- Fits rim hole diameter 0.625"

Milton Industries 1 1/4" Tubeless Tire Valve MIL 415-50

Milton Industries 1 1/4" Tubeless Tire Valve MIL S415

