

AIR/POWER TOOLS & ACCESSORIES

AIR COMPRESSORS

- 165 max psi
- Stainless steel valves
- No mag starter required
- Splash lubricated
- 5 Horsepower
- 220 Volt 1 phase power
- 15.3 CFM @ 100 psi
- 2 Year warranty

Belaire Compressors Two Stage Electric Air Compressor, 60 Gallon BAC 216V



- This Powermate 60 Gallon air compressor provides excellent power and run times to air tools thanks to a large tank delivering 11.5 CFM at 90 psi.
- The compressor features a 3.7 HP motor that operates on 230 volts and a cast-iron, twin cylinder pump which is oil lubricated for a long performance life.
- 155 PSI max pressure for optimum tool performance

Powermate 60 Gallon Stationary Electric Air Compressor COM PLA3706056



- Heavy duty induction motor for maximum performance and efficiency
- 155 PSI max pressure for optimum tool performance
- Features a cast iron, V-Twin cylinder, oil lubricated pump
- Dual voltage motor is wired for standard 120-Volt outlet, and may also be converted for 240-Volt application
- Fully assembled and equipped with quick-set regulator, tank and tool pressure gauges, quick connect air outlet and on/off switch for ease of use

Powermate 30 Gallon Portable Electric Air Compressor COM PLA1683066



- Heavy duty induction motor for maximum performance and efficiency
- Dual voltage motor is wired for standard 120-volt outlet and may also be converted for 240-volt application
- CFM at 40 psi is 6.2 and CFM at 90 psi is 5.3
- Equipped with quick-set tank and tool pressure gauges, quick connect air outlet and on/off switch

Powermate 20 Gallon Portable Electric Air Compressor COM PP1682066.MN



- 1/3 HP DC Motor
- 3 Gallon pancake tank
- 100 max psi working pressure
- Flip-up handle for easy carrying

Briggs & Stratton 3 Gallon Oil Free Portable Air Compressor AHT 110341



AIR/POWER TOOLS & ACCESSORIES

AIR COMPRESSORS OIL

- Maintains viscosity in the temperature range of 20°F to 440°F
- International Standards Organization velocity grade of 68
- High oxidation resistance

Milton Industries ISO 68 Air Compressor Oil, 32 oz. MIL 1002-32

Milton Industries ISO 68 Air Compressor Oil, 1 Gallon MIL 1002



Image Shown: 1002-32

Image Shown: P08909A

Champion Compressors Air Compressor Oil - ISO 100 Recip Lubricant, 1 Gallon CAC P08909A

Champion Compressors Air Compressor Oil - ISO 100 Recip Lubricant, 1 Quart CAC P09479A



- Compressor lube protects against oxidation, corrosion -foaming and wear of metal parts


Champion Compressors Synthetic Oil CAC P13179A



AIR/POWER TOOLS & ACCESSORIES

AIR COMPRESSORS PARTS

Champion Compressors Quick-Lock Garage Kit 1-2 Bays CAC CGK-1-2



- 1/4" male national pipe thread
- Pop off pressure of 70 pounds per square inch
- Air flow of 70 standard cubic feet per minute

Milton Industries 1/4" MNPT ASME Safety Valve - 70 PSI Pop off Pressure MIL 1090-70



- 1/4" male national pipe thread
- 125 pounds per square inch pop off pressure
- 1 5/8" total length

Milton Industries 1/4" MNPT Non Coded Safety Relief Valve MIL 1095-125



- Bubble tight to 10% of set pop off pressure
- 1/4" Male national pipe thread
- 120 standard cubic feet per minute
- Pop off pressure 125 pounds per square inch

Milton Industries 1/4" MNPT ASME Safety Valve - 125 PSI Pop off Pressure MIL S1090-125

Milton Industries 1/4" MNPT ASME Safety Valve - 125 PSI Pop off Pressure MIL 1090-125



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Bubble tight to 10% of set pop off pressure
- Pop off pressure of 150 pounds per square inch
- 140 standard cubic feet per minute

Milton Industries 1/4" MNPT ASME Safety Valve - 150 PSI Pop off Pressure MIL S1090-150



- 1/4" male national pipe thread
- 150 pounds per square inch pop off pressure
- 1 5/8" total length

Milton Industries 1/4" MNPT Non Coded Safety Relief Valve MIL 1095-150



- 1/4" male national pipe threads
- Bubble tight to 10% of pop off pressure
- Pop off pressure of 200 pounds per square inch
- 170 cubic feet per minute

Milton Industries 1/4" MNPT ASME Safety Valve - 200 PSI Pop off Pressure MIL S1090-200



Milton Industries 1/4" MNPT ASME Safety Valve - 200 PSI Pop off Pressure MIL 1090-200

- 1/4" male national pipe threads
- Maximum of 200 pounds per square inch
- Valve prevents air from leaking out while allowing for air to pass through for inflating

Milton Industries 1/4" NPT Tank Valve MIL S684-4

Milton Industries 1/4" NPT Tank Valve MIL 684-4



- 1/8" male national pipe thread
- Maximum pressure of 200 pounds per square inch
- 1" overall length

Milton Industries 1/8" NPT Tank Valve MIL S684



- 1/2" Male national pipe thread
- 1/8" Female national pipe thread side port
- Maximum working pressure of 450 pounds per square inch
- Maximum temperature of 400 degrees Fahrenheit

Milton Industries 1/2" MNPT Compressor Tank Check Valve MIL S1091-1



- Maximum working pressure with air, water and oil of 400 PSI
- Maximum working pressure with steam of 150 PSI
- Temperature range of -20 degrees Fahrenheit to 350 degrees Fahrenheit


Image Shown: S-1094-8



Milton Industries 1/2" FNPT Full Port Brass Ball Valve MIL S-1094-8

Milton Industries 1/4" FNPT Full Port Brass Ball Valve MIL S-1094-4

- Designed for use with compressed air, water or oil
- 3/8" x 3/8" FNPT
- Maximum working pressure (air/water/oil) 400PSI
- Maximum working pressure steam 150 PSI
- Operating temperature -20° to 350° Fahrenheit



Milton Industries Ball Valve - Full Port - 3/8" x 3/8" MIL S-1094-6

- 1/4" national pipe thread
- Replacement part for compressor tanks
- Brass body, steel handle

Milton Industries 1/4" Compressor Tank Drain Cock MIL S614-4



- Maximum pressure of 150 pounds per square inch
- Air flow of 5 standard cubic feet per minute at 100 pounds per square inch
- Temperature range of 40 degrees Fahrenheit to 140 degrees Fahrenheit

Milton Industries 1/4" NPT Flow Control Valve MIL S638



- Suitable replacement for 2 HP at 120V 1 phase, 3 HP at 240V 1 phase or 5 HP at 240V 3 phase
- 95 to 125 pounds per square inch
- Four 1/4" female national thread pipe port manifold
- UL Listed, CSA certified

Milton Industries Compressor Pressure Switch MIL S1060




- Suitable replacement for 2 HP at 120V 1 phase, 3 HP at 240V 1 phase or 5 HP at 240V 3 phase
- 140 to 175 pounds per square inch
- Four 1/4" female national thread pipe port manifold
- UL Listed, CSA certified

Milton Industries Heavy Duty Compressor Pressure Switch MIL S1062



- 1/4" male national pipe thread
- Includes #638-7 dial gauge
- Maximum pressure of 150 pounds per square inch
- Temperature range of 40 degrees Fahrenheit to 250 degrees Fahrenheit

Milton Industries 1/4" NPT Flow Control Valve with Dial Gauge MIL S638-1



AIR/POWER TOOLS & ACCESSORIES PRESSURE GAUGES

- 1/8" male national pipe thread
- Pressure range of 0 to 160 pounds per square inch
- Working Temperature range of 40° F to 250° F

Milton Industries 1/8" NPT Center Back Mount Pressure Gauge MIL 638-7



- 1/8" male national pipe thread
- Pressure range of 0 to 60 pounds per square inch
- Temperature range of 13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/8" NPT Mini Pressure Gauge MIL 1188



- 1/4" national pipe thread
- Pressure range of 0 to 300 pounds per square inch
- Temperature range of 13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/4" NPT High Pressure Gauge MIL 1192



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

Image Shown: 1193

- 1/4" national pipe thread
- Temperature range of 13 degrees Fahrenheit to 120 degrees Fahrenheit

Milton Industries 1/4" NPT Pressure Gauge, 0 to 60 PSI MIL 1193

Milton Industries 1/4" NPT High Pressure Gauge, 0 to 300 PSI MIL 1195



- 1/4" national pipe thread
- Maximum 20 standard cubic feet per minute
- Operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- Maximum working pressure up to 150 pounds per square inch
- Polycarbonate bowl
- 20 Micron filter
- Overnight drain

Milton Industries 1/4" NPT Polycarbonate Mini Piggyback FR Duo MIL S1142



AIR/POWER TOOLS & ACCESSORIES

FILTERS / REGULATORS

- Has an operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- 1/4" national pipe thread air inlet
- Maximum of 20 standard cubic feet per minute

Milton Industries 1/4" NPT Deluxe FRL Trio MIL S1140



- 1/4" national pipe thread
- Maximum of 150 pounds per square inch
- Maximum of 48 standard cubic feet per minute
- Operating temperature range of 40 degrees Fahrenheit to 150 degrees Fahrenheit
- Filter has overnight drain
- 40 Micron bronze sintered filter

Milton Industries 1/4" NPT Deluxe Polycarbonate FR Duo MIL 1106



- Maximum pressure of 150 pounds per square inch
- Maximum of 48 standard cubic feet per minute at 100 pounds per square inch
- Install upstream from regulators
- Can be set up as a modular unit as well
- 20 Micron Filter

Milton Industries 1/4" NPT Polycarbonate FRL Micro Filter MIL 1018

Milton Industries 3/8" NPT Polycarbonate FRL Micro Filter MIL 1019

Milton Industries 1/2" Micro Filter MIL 1020

Image Shown: 1019



- Maximum pressure of 150 pounds per square inch
- Maximum of 16 standard cubic feet per minute at 100 pounds per square inch
- Operating temperature range of 40 degrees Fahrenheit to 125 degrees Fahrenheit
- Not for use with synthetic lubricants

Milton Industries 1/4" NPT Polycarbonate Precision Lubricator MIL 1028

Milton Industries 3/8" NPT Polycarbonate Precision Lubricator MIL 1029

Milton Industries 1/2" NPT Polycarbonate Precision Lubricator MIL 1030

Image Shown: 1028



- 1/2" national pipe thread
- Maximum of 250 pounds per square inch
- Maximum of 100 standard cubic feet per minute
- Operating temperature range of 40 degrees Fahrenheit to 150 degrees Fahrenheit
- Filter has overnight drain
- 40 Micron bronze sintered filter

Milton Industries 1/2" NPT Deluxe Metal FR Duo MIL 1108



- 1/4" national pipe thread
- Maximum inlet pressure of 150 pounds per square inch
- 1 ounce polycarbonate bowl
- Maximum of 16 standard cubic feet per minute

Milton Industries 1/4" NPT Polycarbonate Mini Lubricator MIL S-1150



- The mini micro filter is ideal for use in compact low air flow applications such as small pneumatic equipment, miniature valving and instruments
- Filter includes a 20 micron filter
- Polycarbonate bowl with auto drain
- Maximum pressure 150 pounds per square inch
- Filter has overnight drain

Milton Industries 1/4" NPT Polycarbonate Mini Filter MIL S-1144



- Maximum pressure of 150 pounds per square inch
- Maximum of 75 standard cubic feet per minute at 100 pounds per square inch
- Install upstream from regulators
- Temperature range of 40 degrees Fahrenheit to 160 degrees Fahrenheit
- 40 Micron bronze sintered filter

Milton Industries 3/8" NPT Metal FRL Filter MIL 1019-8

Milton Industries 1/4" NPT Metal FRL Filter Bowl MIL 1018-8

Milton Industries 1/2" NPT Heavy Duty Metal Filter MIL 1020-8

Image Shown: 1019-8



- 1/2" national pipe thread
- Maximum pressure of 250 pounds per square inch
- Maximum of 115 standard cubic feet per minute at 100 pounds per square inch
- Install upstream from regulators
- Temperature range of 40 degrees Fahrenheit to 160 degrees Fahrenheit
- 40 Micron Filter

Milton Industries 1/2" Metal FRL Filter Bowl MIL 1120-8



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Maximum pressure of 250 pounds per square inch
- Maximum of 230 standard cubic feet per minute at 100 pounds per square inch
- Install upstream from regulators
- Temperature range of 40 degrees Fahrenheit to 160 degrees Fahrenheit
- 40 Micron bronze sintered filter

Milton Industries 3/4" NPT Metal FRL Micro Filter MIL 1022-8

Milton Industries 1" NPT Metal FRL Filter Bowl MIL 1122-8



Image Shown: 1022-8

- 1/2" national pipe thread
- Maximum pressure of 200 pounds per square inch
- Maximum of 142 standard cubic feet per minute at 100 pounds per square inch
- Operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- 40 Micron bronze sintered filter

Milton Industries 1/2" NPT Metal Lubricator - 9 Ounce Bowl MIL 1031-8



- 1/2" national pipe thread
- Maximum pressure of 250 pounds per square inch
- Maximum of 48 standard cubic feet per minute at 100 pounds per square inch
- Install upstream from regulators
- Can be set up as a modular unit as well
- 20 micron bronze sintered filter

Milton Industries 1/2" NPT Metal Micro Filter MIL 1020-6



- 3/8" national pipe thread
- Manual overnight drain
- Includes a 40 micron bronze sintered filter
- 6 ounce bowl capacity
- Site glass to monitor water level

Milton Industries 3/8" NPT Metal Micro Filter MIL 1019-6



- 1/4" national pipe thread
- Auto overnight drain
- Includes sight glass to monitor water levels
- 40 micron bronze sintered filter

Milton Industries 1/4" NPT Metal FRL Micro Filter MIL 1018-6



- 1/4" national pipe thread
- 1/8" national pipe thread gauge ports
- Maximum inlet pressure of 250 pounds per square inch
- Maximum 25 standard cubic feet per minute
- Buna-N seal
- Gauge not included

Milton Industries 1/4" NPT Mini Low Pressure Regulator MIL S1146



Image Shown: 1114

- Maximum of 80 standard cubic feet per minute at 100 pounds per square inch
- Operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- Gauge not included
- Gauge port 1/4"

Milton Industries 3/8" NPT Regulator MIL 1114

Milton Industries 1/2" NPT Regulator MIL 1115



- Maximum of 50 standard cubic feet per minute at 100 pounds per square inch
- Operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- Gauge not included
- Gauge port 1/4"

Milton Industries 1/4" NPT High Pressure FRL Regulator MIL 1113-8

Milton Industries 3/8" NPT High Pressure FRL Regulator MIL 1114-8

Milton Industries 1/2" NPT High Pressure FRL Regulator MIL 1115-8



Image Shown: 1113-8

- 3/4" national pipe thread
- Maximum inlet pressure of 250 pounds per square inch
- Maximum of 220 standard cubic feet per minute at 100 pounds per square inch
- Operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- Buna-N diaphragm
- Gauge not included
- Gauge port 1/4"

Milton Industries 3/4" NPT High Pressure Regulator MIL 1026-8



- Maximum of 150 pounds per square inch
- Maximum of 50 standard cubic feet per minute
- Operating temperature range of 40 degrees Fahrenheit to 160 degrees Fahrenheit
- Metal Bowl

Milton Industries 1/4" NPT Metal Piggyback Filter Regulator MIL 1109

Milton Industries 1/2" NPT Metal Piggyback Filter Regulator MIL 1111

Image Shown: 1109



- Maximum inlet pressure of 250 pounds per square inch
- 1/8" national pipe thread gauge ports
- Maximum of 25 cubic feet per minute
- Operating temperature range of 40 degrees Fahrenheit to 120 degrees Fahrenheit
- Gauge not included
- Gauge port 1/8"

Milton Industries 1/4" NPT Mini Heavy Duty Regulator MIL S1145



- Maximum pressure of 125 PSI
- Maximum flow capacity of 15 standard cubic feet per minute
- Working temperature of 32° F to 130° F
- 1/4" Male and female national pipe threads

Milton Industries Mini Disposable Air Line Desiccant Filter MIL S1173



- Screws on any 1/4" NPT air system
- Extends the life of your tools by removing dirt, dust, water, and oil from air lines
- Uses non-toxic moisture-absorbing silica gel to filter contaminants - safe for the environment and your tools

Tru-Flate® Dessicant Dryer CPM 41-103



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

AIR/POWER TOOLS & ACCESSORIES

TANK CONVERSION KIT

- Converts R-12 Freon tanks to portable air tanks
- Includes filler valve, gauge, 4' air hose assembly, manifold and air chuck
- Not for propane tank conversion

Milton Industries Tank Conversion Kit with 4' Hose Assembly MIL S682



AIR/POWER TOOLS & ACCESSORIES

AIR HOSE REELS

- Vertical or Horizontal mount
- Bend restrictors help keep hose from kinking
- Guided automatic hose rewind system
- 50' Hose Length
- 1/4" MNPT fitting size

Tru-Flate® 50' x 3/8" Hose Reel CPM 588HR-TF



- Auto Retract/Latch Hose Mechanism - Simplifies every job by keeping excess hose out of the work space
- Positive Latching Mechanism - Locks hose automatically in 18" intervals
- Durable Construction - Made from durable UV stabilized polypropylene
- Adjustable Hose Stopper - increase or decrease the length of the hose that remains when hose is fully retracted
- Lead-in Hose Included 3' x 1/4" MNPT.
- Flexzilla hose features extreme all-weather flexibility (-40 to 140°F), won't kink under pressure, and anodized aircraft aluminum fittings

Legacy™ Flexzilla® Enclosed Plastic Retractable Air Hose Reel, 3/8" x 50' LEG L8250FZ



- Featuring Levelwind™ Technology - Legacy's unique winding system that automatically layers hose back and forth across the reel ensuring that the hose is coiled smoothly, easily...every time
- Latching Mode Switch choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding
- Seven Position Locking Bracket - These reels can swivel freely on a mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.
- Adjustable Hose Stopper - increase or decrease the length of the hose that remains when hose is fully retracted
- Extra Large Swivel - A 3/4" swivel reduces flow restrictions and allows for maximum flow
- Free Standing Base - Portable! Use freestanding or mounted on wall or ceiling... flat base allows reel to rest on ground
- Workforce PVC Air Hose features outer cover made from the highest quality PVC materials, temp. range of 15° to 150°F, and corrosion-resistant solid brass NPT fittings

Legacy™ Levelwind™ Retractable Air Hose Reel, 3/8" x 100' LEG L8310



- Featuring Levelwind™ Technology - Legacy's unique winding system that automatically layers hose back and forth across the reel ensuring that the hose is coiled smoothly, easily...every time - and includes Flexzilla® air hose and lead-in hose.
- Latching Mode Switch choose from latching hose every 3' for extended use or switch to free run for immediate automatic rewinding
- Seven Position Locking Bracket - These reels can swivel freely on a mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.
- Adjustable Hose Stopper - increase or decrease the length of the hose that remains when hose is fully retracted
- Extra Large Swivel - A 3/4" swivel reduces flow restrictions and allows for maximum flow
- Free Standing Base - Portable! Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on ground
- Flexzilla hose features extreme all-weather flexibility (-40 to 140°F), won't kink under pressure, and anodized aircraft aluminum fittings



Image Shown:
L8305FZ

Legacy™ Flexzilla® Retractable Air Hose Reel, 3/8" x 50' LEG L8305FZ

Legacy™ Flexzilla® Retractable Air Hose Reel, 3/8" x 75' LEG L8306FZ

Legacy™ Flexzilla® Retractable Air Hose Reel, 1/2" x 50' LEG L8335FZ

This auto retractable, open face hose reel is ideal for indoor shop, mobile and industrial applications.

Reel Features:

- Multi-Position Guide Arm - Allows mounting on wall, tank or overhead
- Durable Heavy-Duty Steel Construction - Provides strength and stability to the reel and bracket
- Corrosion-Resistant Powder Coating - Provides extra measure of protection against the elements
- Four-Way Direction Rollers - Allow the hose to be easily pulled from the reel
- Self-Locking Fasteners - Stay tight even in mobile installations
- Narrow Size - Ideal for easy placement and storage
- Multi-Position Release Ratchet - Allows appropriate amount of hose to be extended for each job site
- Metal Latching Pawl - Makes an audible clicking sound allowing the latching zone to be locked quickly and easily
- Fully-Enclosed Spring Motor - Packed with grease for extended life
- Lead-in Hose Included - 5 ft. x 1/4 in. MNPT x 1/4 in. NPSM female swivel



Flexzilla® Air Hose Features:

- Extreme all-weather flexibility, even in subzero temperatures (-40° to 140°F)
- Won't kink under pressure
- Lightweight and easy to handle
- Lays flat - no memory
- Durable and abrasion-resistant outer cover
- Anodized aircraft aluminum ends
- Max. working pressure at 70°F: 300 psi
- Includes bend restrictor to reduce wear and tear, prolonging the life of the hose

Legacy™ Flexzilla® Retractable Air Hose Reel, Open Face, Single Axle Arm, 3/8" x 50' LEG L8611FZ

- Dual Arm Steel - "Industrial Grade" Reel
- Samson hose reels are available in high, medium and low pressure applications. Different hose capacities for maximum flexibility in selecting a hose reel assembly to match specific need. Samson hose reels are designed with non-restrictive fluid passages and the right hose diameter for each application to provide the quickest material delivery.
- 3000 PSI Rating
- Includes Inlet Connection Hose
- Application: Air, Water, Antifreeze, Windshield Wash



Samson Heavy Duty Double Pedestal Arm Hose Reel - 50' x 3/8" - 300 PSI Rating 3/8" NPT Outlet Thread SAM 504151

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Dual Arm Steel - "Industrial Grade" Reel
- Samson hose reels are available in high, medium and low pressure applications. Different hose capacities for maximum flexibility in selecting a hose reel assembly to match specific need. Samson hose reels are designed with non-restrictive fluid passages and the right hose diameter for each application to provide the quickest material delivery.
- 2000 PSI Rating
- Includes Inlet Connection Hose
- Application: Oil, functional fluids



Samson Heavy Duty Double Pedestal Arm Hose Reel - 50' x 1/2" - 2000 PSI Rating 1/2" NPT Outlet Thread SAM 504250

- Aluminum base and arms with composite spool hose reel.

Samson 50' x 3/8" NPTM Air Reel SAM 506121



- Five-position adjustable outlet roller arm
- Spring powered automatic recoil
- Angled hose guide for smooth, parallel hose pull-out and retraction
- An eight-position ratchet gearing that locks the reel at the desired hose length
- Slotted mounting base for easy installation

Lincoln Industrial Value Series Air and Water Reel Assembly, 3/8" x 50' LJ 83753

Lincoln Industrial Value Series Air and Water Reel Assembly, 1/2" x 50' LJ 83754



Image Shown: 83753


- Allows vertical/horizontal mounting
- Can hold up to 100 feet of 3/8" hose
- Durable steel reel

Tru-Flate® Manual Hose Reel CPM 503HR-RET



- Versatile installation means the reel can be fastened in any direction, on a bench, under a bench, on a wall, from the ceiling, on a compressor or on a service truck. Base has a six hole pattern for bench mounting and a center line pattern for mounting on a stud wall.
- Supplies 28 CFM at 90 PSI. Reel holds 150 feet of 5/8" OD hose or 100 feet of 3/4" OD hose.
- Dimensions: Diameter 17 3/4", Width 11", Height 19" Coil and uncoil your air hose neatly and quickly to prevent damage.
- The Side Winder air hose reel provides a large 10" diameter reel to prevent tight coils in your air hose.
- Two built-in tool hangers keep your air chuck, blow gun or other air tools handy. The constant supply 1/4" NPT brass swivel keeps air flowing freely and handles up to 250 PSI even when dispensing or winding air hose. A coil spring brake keeps reel from unrolling, yet allows easy dispersion.

Lisle Side Winder Air Hose Reel LST 50350



- Hose type - RMA Class A and 74
- Size - 11/16" to 23/32"

Lincoln Industrial Adjustable Ball Stop LJ 85516

Lincoln Industrial Adjustable Ball Stop LJ 85517

Image Shown: 85516



AIR/POWER TOOLS & ACCESSORIES

AIR HOSES

- 1/4" x 25', 1/4" NPT Male Swivel Strain Relief Fittings
- Constructed of Lightweight, Tough Polyurethane
- High Quality Brass Fittings Provide Strong & Durable Connection
- Strain Relief Fittings are Completely Field Repairable
- Made in USA

CARQUEST Flexcoil, 1/4" x 25', 1/4" NPT Swivel Strain Relief Fittings, Blue CPE 31550



- Constructed of Nylon Resin, Resists Moisture & Abrasion
- Temperature Range: -60°F to +200°F
- High Quality Brass Fittings Provide Strong & Durable Connection
- All Coils are Equipped with Spring Strain Reliefs

CARQUEST Nylon Coil, 1/4" x 12', 1/4" NPT Swivel Fittings, Yellow CPE 31560

CARQUEST Nylon Coil, 1/4" x 25', 1/4" NPT Swivel Fittings, Yellow CPE 31561

CARQUEST Nylon Coil, 1/4" x 50', 1/4" NPT Swivel Fittings, Yellow CPE 31562

CARQUEST Nylon Coil, 3/8" x 25', 1/4" NPT Swivel Fittings, Yellow CPE 31565

CARQUEST Nylon Coil, 3/8" x 50', 1/4" NPT Swivel Fittings, Yellow CPE 31566

CARQUEST Nylon Coil, 3/8" x 25', 3/8" NPT Swivel Fittings, Yellow CPE 31570

CARQUEST Nylon Coil, 3/8" x 50', 3/8" NPT Swivel Fittings, Yellow CPE 31571



Image Shown: 31560

- Easy storage
- 32 F to 120 F temperature range
- 200 PSI working pressure
- 25' Length
- Swivel Fittings reduce hose twist

Tru-Flate® 25' x 1/4" Nylon Recoil Hose CPM 4-25E-RET



- 3/8" hose inside diameter
- Working temperature range of -40°F to 180°F
- Yellow PVC tubing
- 1/4" male pipe fittings

Milton Industries 3/8" x 25' Rekoil Hose MIL 1674-4



- Cold weather flexibility
- -30°F to 150°F temperature range
- Easy storage
- 50' Length
- Bend restrictors help keep hose from kinking

Tru-Flate® 50' x 1/4" Poly Recoil Hose CPM 24-50E-TF



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

Flexzilla® is a revolutionary hose featuring a Flexible Hybrid Polymer material that redefines flexibility. This engineered polymer-blend material permits use in environments where general purpose PVC and rubber hose may become too stiff. Flexzilla hose characteristics offer zero memory allowing it to lay flat. It won't work against you during operation and coils easily after use. Flexzilla offers extreme all-weather flexibility, even in subzero conditions, and is ideal in both hot and cold environments where tight radius bends are needed.

Image Shown: HFZ3825YW2



Features:

- Extreme all-weather flexibility, even in subzero temperatures (-40° to 140°F)
- Won't kink under pressure
- Lightweight and easy to handle
- Lays flat - no memory
- Durable and abrasion-resistant outer cover
- Anodized aircraft aluminum ends
- Max. working pressure at 70°F: 300 psi
- Includes bend restrictors to reduce wear and tear, prolonging the life of the hose

Legacy™ Flexzilla® Air Hose, 1/2" x 50', 3/8" MNPT Fittings
LEG HFZ1250YW3-N

Legacy™ Flexzilla® Air Hose, 3/8" x 25', 1/4" MNPT Fittings
LEG HFZ3825YW2

Legacy™ Flexzilla® Air Hose, 3/8" x 50', 1/4" MNPT Fittings
LEG HFZ3850YW2-N

Flexzilla® Pro Field Repairable Air Hose features extreme all-weather flexibility, rugged durability and won't kink under pressure. Its unique Flexible Hybrid Polymer material redefines flexibility. With reusable anodized aircraft aluminum fittings, the Flexzilla Pro Air Hose can be repaired on the job site in a few simple steps.



Image Shown:
HFZP3825YW2

Features:

- Field Repairable – Reusable anodized aircraft aluminum fittings
- Extreme all-weather flexibility, even in subzero temperatures (-40° to 140°F)
- Won't kink under pressure
- Lightweight and easy to handle
- Lays flat - no memory
- Durable and abrasion-resistant outer cover
- Max. working pressure at 70°F: 300 psi
- Flexzilla Pro Reusable Fittings include bend reinforcement to reduce wear and tear, prolonging the life of the hose

Legacy Flexzilla® Pro Air Hose, 3/8" x 25', 1/4" MNPT Fittings
LEG HFZP3825YW2

Legacy Flexzilla® Pro Air Hose, 3/8" x 50', 1/4" MNPT Fittings
LEG HFZP3850YW2

- Outer cover and inner tube are made from the highest quality PVC materials
- Temp. Range: 15° to 150°F
- Twin Spiral Braiding - Extra strong polyester textile cord adds reinforcement to inner tube
- Cover is oil and abrasion-resistant and non-marring
- Includes bend restrictors that reduces wear and tear, prolonging the life of the hose



Image Shown: HWF3850BL2

Legacy Workforce® Air Hose, 3/8" x 50', 1/4" Fittings, Blue, PVC LEG HWF3850BL2

Legacy Workforce Air Hose, 1/4" x 25', 1/4" Fittings, Blue, PVC LEG HWF1425BL2

Flexzilla® is a revolutionary hose featuring a Flexible Hybrid Polymer material that redefines flexibility. This engineered polymer-blend material permits use in environments where general purpose PVC and rubber hose may become too stiff. Flexzilla hose characteristics offer zero memory allowing it to lay flat. It won't work against you during operation and coils easily after use. Flexzilla offers extreme all-weather flexibility, even in subzero conditions, and is ideal in both hot and cold environments where tight radius bends are needed.



Why use a Whip Hose?

- Increased longevity of the main hose
- Reduces user fatigue by eliminating weight of coupler/plug
- Ball swivel increases mobility in tight spaces
- Improves air tool ergonomics

Features:

- Extreme all-weather flexibility, even in subzero temperatures (-40° to 140°F)
- Won't kink under pressure
- Lightweight and easy to handle
- Lays flat - no memory
- Durable and abrasion-resistant outer cover
- Anodized aircraft aluminum ends
- Max. working pressure at 70°F: 300 psi
- Includes bend restrictor to reduce wear and tear, prolonging the life of the hose
- 360° ball swivel 30° tilt in any direction

Legacy™ Flexzilla® Whip Hose with Ball Swivel, 3/8" x 2' LEG HFZ3802YW2B

- Great for general purpose tasks
- 20°F to 145°F temperature range
- 300 PSI working pressure
- 50' Length
- Bend restrictors help keep hose from kinking

Tru-Flate® 50' x 3/8" PVC Air Hose
CPM 576-50A



- Excellent cold weather flexibility
- -40°F to 150°F temperature range
- 300 PSI working pressure
- 50' Length
- Bend restrictors help keep hose from kinking

Tru-Flate® 50' x 3/8" Ultra Air® Hybrid Air Hose
CPM 575-50A



- Cold weather flexibility
- -30°F to 150°F temperature range
- 300 PSI working pressure
- 25' Length
- Bend restrictors help keep hose from kinking
- Swivel fittings help reduce hose twist

Tru-Flate® 25' x 1/4" Poly Air Hose CPM 12-25E



- Good durability
- -20°F to 165°F temperature range
- 300 PSI working pressure
- 50' Length
- Bend restrictors help keep hose from kinking

Tru-Flate® 50' x 3/8" Rubber Air Hose
CPM 552-50AE



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Designed for tough service station and shop applications with impact air tools.
- This hose features heavy-duty, four-spiral construction with a polyester reinforcement that keeps the hose flexible in the most punishing conditions.
- The EPDM rubber construction offers superior durability to resist abrasion and weathering.
- This limited oil resistant hose is designed for a working pressure of 250 psi and is made in the USA.



Image Shown: 31660

HBD Industries Professional Rubber Air Hose, 25', 1/4" ID, 1/4" Male NPT CPE 31660

HBD Industries Professional Rubber Air Hose, 50', 1/4" ID, 1/4" Male NPT CPE 31661

HBD Industries Professional Rubber Air Hose, 25', 3/8" ID, 1/4" Male NPT CPE 31662

HBD Industries Professional Rubber Air Hose, 50', 3/8" ID, 1/4" Male NPT CPE 31663

HBD Industries Professional Rubber Air Hose, 25', 1/2" ID, 1/2" Male NPT CPE 31664

HBD Industries Professional Rubber Air Hose, 50', 1/2" ID, 1/2" Male NPT CPE 31665

- Designed for service station and shop applications.
- It features a two-spiral construction with a polyester reinforcement that provides excellent durability and is extremely flexible.
- The limited oil resistant EPDM tube and cover offers superior resistance to abrasion and weathering.
- This hose is designed for a working pressure of 200 psi and is made in the USA.



Image Shown: 31675

HBD Industries Heavy-Duty Rubber Air Hose, 25', 1/4" ID, 1/4" Male NPT CPE 31675

HBD Industries Heavy-Duty Rubber Air Hose, 50', 1/4" ID, 1/4" Male NPT CPE 31676

HBD Industries Heavy-Duty Rubber Air Hose, 25', 3/8" ID, 1/4" Male NPT CPE 31677

HBD Industries Heavy-Duty Rubber Air Hose, 50', 3/8" ID, 1/4" Male NPT CPE 31678

AIR/POWER TOOLS & ACCESSORIES

SNUBBER & WHIP HOSES

- Maximum working pressure of 200 pounds per square inch
- 1/4" hose inside diameter
- 1/4" Male national pipe thread

Milton Industries 30" 1/4" ID Snubber Hose MIL S680



- Maximum working pressure of 250 pounds per square inch
- 1/4" hose inside diameter
- 1/4" Male national pipe thread

Milton Industries 5 Foot 1/4" ID Snubber Hose MIL S680-1



- 1/4" male national pipe thread
- 3/8" hose inside diameter
- Maximum working pressure of 200 pounds per square inch

Milton Industries 5 Foot 3/8" ID Snubber Hose MIL S680-3



- Maximum working pressure of 200 pounds per square inch
- Burst pressure of 800 pounds
- 3/8" hose inside diameter
- A must for impact tools

Milton Industries 30 Inch 3/8" ID Snubber Hose MIL S680-2



- Replacement part
- Used to replace hose whip on Milton inflator gauge #506
- 1/8" -27 threads NPT
- 10 to 160 pounds per square inch

Milton Industries 15" Replacement Hose Whip MIL 509



AIR/POWER TOOLS & ACCESSORIES

HOSE REPAIR

Flexzilla® Pro Reusable Fittings and Splicers allow you to quickly repair Flexzilla hose on the job site or create a custom length hose in just three easy steps.

Features:

- Reusable, anodized aircraft aluminum fitting
- Easily repair your hose in 3 easy steps:
- Cut away damaged portion of the hose
- Install the fitting onto the hose
- Tighten the fitting nuts until snug



Legacy Flexzilla® Pro Air Hose Reusable Fitting, 3/8" Barb, 1/4" MNPT LEG RP900375

- Brass Construction
- Swivel Fittings Feature Factory Applied Thread Sealant
- Made in USA

Acme Automotive Nylon Coil Swivel Male, 1/4" ID x 1/4" MPT CPE 31580



- 1/4" hose inside diameter
- Hose clamps for 5/8" hose outside diameter
- 1/4" Female air chuck

Milton Industries 1/4" ID Hose Repair Kit MIL S620



Image Shown: 604

- 1/2" hose inside diameter
- Features a barb type construction that provides a secure grip on the hose inside diameter

Milton Industries 3/8" MNPT 1/2" ID Hose End Fitting MIL 604

Milton Industries 1/2" MNPT 1/2" ID Hose End Fitting MIL 604-1



- Rust/Corrosion resistant
- Durable material
- Easy fit
- Perfect for field repairs

Image Shown: 21-123

**Tru-Flate® 1/4" ID x 1/4" MNPT Hose Fitting** CPM 21-123**Tru-Flate® 3/8" ID x 1/4" MNPT Hose Fitting** CPM 21-143

- 19/16" or 19/32" hose outside diameter
- 1/4" or 5/16" hose inside diameter
- Maximum air pressure of 250 pounds per square inch

**Milton Industries 1/4" MNPT 19/16" or 19/32" OD Reusable Hose End Fitting** MIL S615

- Can be used with both 1/4" inner diameter (5/8" outer diameter) and 5/16" inner diameter (5/8" outer diameter) hose
- 1/4" Male national pipe thread
- Maximum air pressure 250 pounds per square inch

**Milton Industries 1/4" MNPT, 5/8" OD Reusable Hose End Fitting** MIL S617

- 1/4" male national pipe thread
- 11/16" hose outside diameter
- 1/4" national pipe thread

**Milton Industries 1/4" MNPT 11/16" OD Reusable Hose End Fitting** MIL 621-11

- 1/2" hose inside diameter
- For best results and professional finished product the hose end should be secured with a crimped ferrule
- Maximum pressure of 250 pounds per square inch

**Milton Industries 1/2" ID Hose Mender Fitting** MIL 642-1

- Durable material
- Perfect fit
- Ideal for quick repairs

Image Shown: 21-423

**Tru-Flate® 1/4" ID Hose Splicer** CPM 21-423**Tru-Flate® 3/8" ID Hose Splicer** CPM 21-467

- Full 360 degree swivel hose end helps eliminate kink and twisted airlines.
- Steel construction with black oxide finish. 1/4" male end; 1/4" NPT female swivel end

**Milton Industries 1/4" Full Swivel Hose End** MIL S659

- For best results, use the Milton hose ferrule crimping tool #1626
- For use with brass ferrules

Image Shown:
1654-5**Milton Industries 1/2" OD Brass Hose Ferrule** MIL 1654-2**Milton Industries 9/16" OD Brass Hose Ferrule** MIL 1654-3**Milton Industries 19/32" OD Brass Hose Ferrule** MIL 1654-4**Milton Industries 5/8" OD Brass Hose Ferrule** MIL 1654-5**Milton Industries 21/32" OD Brass Hose Ferrule** MIL 1654-6**Milton Industries 11/16" OD Brass Hose Ferrule** MIL 1654-7**Milton Industries 23/32" OD Brass Hose Ferrule** MIL 1654-8**Milton Industries 3/4" OD Brass Hose Ferrule** MIL 1654-9**Milton Industries 7/8" OD Brass Hose Ferrule** MIL 1654-12

- Used to produce professional quality hose assemblies
- Fast and easy for convenience
- Ferrule provides a permanent connection to the hose and fitting

Milton Industries Hose Ferrule Crimping Tool MIL 1626

AIR/POWER TOOLS & ACCESSORIES

AIR CHUCKS

- Built-in Shut-Off valve
- 150 PSI maximum
- Durable material is rust and corrosion resistant
- 1/4" Female NPT

**Tru-Flate® Ball Foot Air Chuck** CPM 17-351

- Designed and manufactured to exacting standards
- Closed/sealing type chuck
- 1/4" Female national pipe thread
- 1/4" hose inside diameter

**Milton Industries 1/4" Single Head Air Chuck** MIL S699

- Built-in Shut-Off valve
- 150 PSI maximum
- Durable material is rust and corrosion resistant
- 1/4" Female NPT

**Tru-Flate® Ball Foot Air Chuck With Clip** CPM 17-353

- Grip chuck included
- 1/4" Female national pipe thread
- For tire machines

**Milton Industries 1/4" FNPT Tire Machine Grip Chuck** MIL 598

- Fits all standard single head air chucks
- Locks onto valve core threads
- Maximum air pressure of 150 pounds per square inch

**Milton Industries Safety Grip Clip Air Chuck** MIL S692

- 1/4" female national pipe thread
- Maximum air pressure of 150 pounds per square inch
- Not for use with inflator gauge

**Milton Industries 1/4" FNPT Single Head Air Chuck with Grip** MIL S698

- Designed and manufactured to exacting standards
- Closed/sealing type chucks
- Not for use with an inflator gauge
- Maximum air pressure of 150 pounds per square inch
- 1/4" hose inside diameter

**Milton Industries 1/4" ID Hose Barb Air Chuck** MIL S695

- 1/4" female national pipe thread
- Closed/sealing type chucks
- Maximum inlet pressure of 150 pounds per square inch
- Not for use on Milton inflator gauges

**Milton Industries 1/4" FNPT Kwik Grip Safety Chuck** MIL S696


* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- 1/4" female national pipe thread
- Maximum air pressure of 150 pounds per square inch
- Closed/sealing type air chuck
- These are not for use with an inflator/pressure gauge.



Milton Industries 1/4" FNPT Straight Head Air Chuck MIL 691

- 1/4" female national pipe thread
- Maximum air pressure of 150 pounds per square inch
- 1/4" hose inside diameter
- Not for use on Milton inflator gauges
- Designed and manufactured to exacting standards



Milton Industries 1/4" ID Euro Style Hose Barb Air Chuck MIL S697

Milton Industries 1/4" ID Euro Style Hose Barb Air Chuck MIL 697

- 1/8"-27 national pipe thread
- Replacement part
- Dual head air chuck



Milton Industries 1/8"-27 NPT Dual Air Chuck Head Replacement MIL 500-4

- Standard dual foot extension for valves on tractors, trucks, or buses
- Built-in shut off valve
- 1/4" Female NPT



Tru-Flate® Dual Foot Air Chuck, 6" CPM 17-383

- Comes with threaded deep well lock nut which locks on valve when tilted
- Built-in shut off valve
- 1/4" Female NPT



Tru-Flate® Locking Dual Foot Air Chuck, 6" CPM 17-395

- DESIGNED/MANUFACTURED: To exacting standards. This is a Closed/Sealing-type air chuck for use on a compressed airline.
- DUAL HEAD CHUCK: Makes tire valves more accessible with the two heads for easier access.
- INFLATE: By hooking the closed head (w/valve) directly to an airline.
- EASY ACCESS: To inner dual when valve is facing inward. Great for reaching into Dually trucks and other challenging angles.
- MAX PSI: Maximum air pressure of 150 pounds per square inch. 1/4" female national pipe thread.



Milton Industries 1/4" FNPT Dual Head Air Chuck MIL S690

- 1/4" female national pipe thread
- Designed and manufactured to exacting standards
- Maximum air pressure of 150 pounds per square inch
- 5 1/4" Extension



Milton Industries 1/4" Straight Foot Dual Head Air Chuck MIL S693

Milton Industries 1/4" Straight Foot Dual Head Air Chuck MIL 693

- 1/4" female national pipe threads
- Both ends lock on valve core threads
- Maximum pressure of 150 pounds per square inch
- 12" Extension



Milton Industries 1/4" FNPT Extended Reach Dual Head Air Chuck MIL S-693-12

AIR/POWER TOOLS & ACCESSORIES

BLO-GUNS

- Durable lightweight aluminum body
- OSHA compliant safety nozzle
- Ergonomic grip provides maximum comfort and control
- 40 CFM of air flow to get projects done faster and easier



Tru-Flate® HI FLO® Safety Blowgun with Rubber Tip CPM 18-607

- Lightweight
- Ergonomic design reduces user fatigue
- Brass valving and bushing ensure long life



Tru-Flate® Pistol Grip Plastic Blowgun CPM 18-325

- 1/4" national pipe thread brass air inlet
- 16.5 standard cubic feet per minute
- Offers up to 90 pounds per square inch
- Lightweight design
- Includes the patent pending universal Kwik Change tip system



Milton Industries Safety Tip Blow Gun Kit MIL S-174KIT

- Maximum working pressure of 150 pounds per square inch
- 10.0 standard cubic feet per minute at 100 pounds per square inch
- 1/4" national pipe thread air inlet
- 1/8"-27 NPS nozzle thread
- Convenient hang hook



Milton Industries 1/4" NPT Pistol Grip Blow Gun MIL S160

- Compact hand-held unit can be used anywhere with compressed air.
- Streamlined comfort fit and full volume control.
- Maximum working pressure: 150 PSI. Maximum nozzle pressure: 30 PSI when dead ended.
- Zinc die cast body Safety blow gun meets OSHA requirements of special relief holes in nozzle which limits pressure to 30 PSI when dead ended (static pressure).
- For use on regulated compressed air lines maximum PSI 150. Many uses such as cleaning fuel and oil lines, or air cleaners, drying out wet ignition systems and spark plugs or blowing out dirt fillings and metal chips.



Milton Industries Safety Button Blow Gun MIL S107

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Use anywhere with compressed air.
- Full flow control.
- Extra large hang-up hook for easy storage.
- Maximum inlet pressure: 150 PSI.
- Maximum nozzle pressure: 30 PSI when dead ended SCFM 10.6 @ 100 PSI.
- 1/4" NPT air inlet, nozzle thread 1/8"-27. Zinc die-cast body, steel plated handle. OSHA compliant.



Milton Industries OSHA Safety Lever Blow Gun with Hang Up Hook MIL S120

- 1/4" national pipe thread air inlet
- Maximum working pressure of 150 pounds per square inch
- 14 standard cubic feet per minute at 100 pounds per square inch



Milton Industries Siphon Spray Blow Gun Kit MIL S157

- Maximum working pressure of 150 pounds per square inch
- 1/4" national pipe thread air inlet
- 11.4 standard cubic feet per minute at 100 pounds per square inch



Milton Industries 1/4" Rubber Tipped Lever Blow Gun MIL S153

- Comes with a 45 degree bend
- Maximum working pressure of 150 pounds per square inch
- 1/4" air inlet
- Offers a tight fit
- 11.4 Standard cubic feet per minute at 100 pounds per square inch



Milton Industries 1/4" Rubber Tipped Blow Gun MIL S154

- For use with liquids
- 1/4" national pipe thread air inlet
- Maximum pressure of 150 pounds per square inch



Milton Industries 1/4" Siphon Spray Blow Gun MIL S156

- 1/4" national pipe thread air inlet
- Maximum working pressure of 150 pounds per square inch
- 10 standard cubic feet per minute at 100 pounds per square inch
- Thread nozzle measures 7/16"-27
- Zinc Alloy body



Milton Industries 1/4" NPT Lever Style Blow Gun MIL S150

- 1/4" female national pipe threads
- Maximum working pressure of 150 pounds per square inch
- 24.5 standard cubic feet per minute at 100 pounds per square inch
- Maximum temperature of 200 degrees Fahrenheit



Milton Industries 1/4" NPT Lever Style Blow Gun Control Valve MIL 151

- Oil Resistant
- Ideal for cleaning fuel lines, air passages, and carburetors
- Safety nozzle connected limiting air pressure to 30 PSI and meeting OSHA safety standards
- Convenient hang hole, comfortable lever



Tru-Flate® Safety Blowgun with Rubber Tip CPM 18-215

- Includes both safety nozzle and rubber nozzle
- 1/4" national pipe thread air inlet
- Rubber tip has a 12.9 standard cubic feet per minute at 100 pounds per square inch
- Safety tip has an 11.7 standard cubic feet per minute at 100 pounds per square inch
- Maximum working pressure of 150 pounds per square inch



Milton Industries 1/4" NPT Lever Style Blow Gun MIL S148

- Easy grip two finger control to adjust from full volume air flow to complete shut-off.
- Knurled grip for secure handling even with oily or greasy fingers.
- Always keep one handy with included shirt pocket clip.
- Fits A-style or any 1/4" ARO 210 style coupler



Image Shown: S116

Milton Industries Pocket Blow Gun Fits Milton A or Any 1/4" Coupler MIL S116

Milton Industries Pocket Blow Gun Fits T Style or 1/4" Tru-Flate MIL S117

- Fits 1/4" body couplers
- Maximum inlet pressure of 150 pounds per square inch
- Air flow of 15.9 standard cubic feet per minute at 100 pounds per square inch
- Includes a clip to easily secure blow gun to your pocket
- Lightweight design



Milton Industries Adjustable M Style Pocket Blow Gun MIL S115


- Great for filling radiators and other containers
- NPT: 1/4" female national pipe threads
- MAXIMUM: Operating pressure range of 30 to 35 pounds per square inch
- MATERIAL: Stainless steel springs, zinc alloy body and nitrile rubber hose
- Made in USA



Milton Industries 1/4" NPT Rubber Filler Spout Faucet MIL S-209

Milton Industries 1/4" NPT Rubber Filler Faucet Spout MIL 209

- 1/4" national pipe thread
- 4.5 standard cubic feet per minute at 100 pounds per square inch
- Maximum pressure of 150 pounds per square inch
- Classified by UL to OSHA standards 29CFR1910.95 and 29CFR1910.242(b)



Milton Industries Safety Blow Gun and 15" Extension MIL 134

- 1/4" national pipe thread air inlet
- Maximum working pressure of 150 pounds per square inch
- Safety nozzle offers 10.5 standard cubic feet per minute at 100 pounds per square inch
- Rubber tip offers 11.6 standard cubic feet per minute at 100 pounds per square inch



Milton Industries 1/4" Lever Style Blow Gun & 2' Extension MIL 158

- Maximum working pressure of 125 pounds per square inch
- 11 standard cubic feet per minute at 90 pounds per square inch
- 1/4" national pipe thread inlet
- Comfort grip squeeze handle allows for variable air volume



Milton Industries 1/4" NPT Pistol Grip Blow Gun with 11" Bent Nozzle MIL S-177



- 1/4" national pipe thread air inlet
- Maximum working pressure of 150 pounds per square inch
- Safety nozzle offers 10.5 standard cubic feet per minute at 100 pounds per square inch
- Rubber tip offers 11.6 standard cubic feet per minute at 100 pounds per square inch

Milton Industries 1/4" NPT Lever Style Blow Gun and 4' Extension MIL 159

- Fits most 6mm blow gun nozzle

Milton Industries Metal Venturi Blow Gun Nozzle MIL S-160X5A



- Replacement for 7/16"-27
- Offers a tight fit
- 1/8" national pipe thread



Milton Industries 7/16"-27 Blow Gun Replacement Rubber Tip MIL 152

AIR/POWER TOOLS & ACCESSORIES

AIR ACCESSORY KITS

- 1/4" I/M Tru-Match® Couplers and Plugs
- 23' x 1/4" Poly Recoil Hose
- 50 PSI Tire Gauge and Ball Foot Chuck
- Blowgun Kit with Multiple Nozzles
- Complete with Storage Box



Tru-Flate® 15 Piece Air Compressor Kit CPM 41-253

- 1/4" I/M Couplers and Plugs
- 1/4" Air Fittings and Thread Sealant Tape
- 50 PSI Tire Gauge and Two Chucks
- Blowgun Kit with Multiple Nozzles
- Complete with Storage Box



Tru-Flate® 20 Piece Air Accessory Kit CPM 41-225

- Includes 1 male hose end, male hose mender, female hex coupler, male hex nipple, female air chuck, tire gauge, blow gun adapter and blow gun inflator pin
- Includes 4 female M style couplers
- Includes 3 male M style couplers
- Basic flow size of 1/4"



Milton Industries M Style Compressor Starter Kit 16 Piece MIL S220

AIR/POWER TOOLS & ACCESSORIES

COUPLERS & PLUGS

- 1/4" body size
- Interchangeable with most manufacturers
- Maximum of 40 standard cubic feet per minute
- Maximum temperature of 250 degrees Fahrenheit
- Maximum 300 pounds per square inch



Milton Industries 1/4" NPT M Style Coupler and Plug Kit - 12 Piece MIL S-210

- Increased airflow to provide maximum torque and optimal performance
- Push-To-Connect for easy connect/disconnect
- Made from Lightweight Durable T6 Aluminum
- Includes one (1) Male Coupler, two (2) Female Couplers, three (3) Female Plugs, and four (4) Male Plugs - 1/4" NPT



Tru-Flate® HI FLO® Coupler and Plug Kit, 10 Piece CPM 13-907

- HI FLO® increases air flow to ensure maximum torque and optimal performance
- Push-To-Connect for easy connect/disconnect
- Made from Lightweight Durable T6 Aluminum
- Includes one (1) Female Coupler, one (1) Female Plug, and two (2) Male Plugs - 1/4" NPT



Tru-Flate® 4 Piece HI FLO® Coupler/Plug Set CPM 13-903

- Increased flow to ensure maximum torque and optimal performance
- 360° swivel helps air hose from kinking
- Lightweight aluminum body helps reduce use fatigue
- 1/4" Male NPT



Tru-Flate® HI FLO® Swivel Plug CPM 12-929

- Durable and high scratch resistant Anodized Purple Aluminum
- V Style (Hi-Flo) Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Provides tools and applications 70% more air-flow and power
- Allows matching of couplers for dedicated hose applications



Milton Industries ColorFit-Mega-Flow Coupler & Plug Kit (7 Piece), Hi-Flo V-Style 1/4" NPT Purple MIL S-307VKIT

- Durable and high scratch resistant Anodized Purple Aluminum
- V Style (Hi-Flo) Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Provides tools and applications 70% more air-flow and power
- Allows matching of couplers for dedicated hose applications



Milton Industries ColorFit-Mega-Flow Coupler & Plug Kit (3 Piece), Hi-Flo V-Style 1/4" NPT Purple MIL S-303VKIT

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Durable and high scratch resistant Anodized Red Aluminum
- M Style (M/Industrial) Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Allows matching of couplers for dedicated hose applications
- Easy to push to connect Air Compressor Accessories



Milton Industries ColorFit Coupler & Plug Kit (7 Piece), M-Style 1/4" NPT Red MIL S-307MKIT

- Durable and high scratch resistant Anodized Red Aluminum
- M Style (M/Industrial) Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Allows matching of couplers for dedicated hose applications
- Easy to push to connect Air Compressor Accessories



Milton Industries ColorFit Coupler & Plug Kit (3 Piece), M-Style 1/4" NPT Red MIL S-303MKIT

- Durable and high scratch resistant Anodized Green Aluminum
- A Style (ARO) Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Allows matching of couplers for dedicated hose applications
- Easy to push to connect Air Compressor Accessories



Milton Industries ColorFit Coupler & Plug Kit (7 Piece), A-Style 1/4" NPT Green MIL S-307AKIT

- Durable and high scratch resistant Anodized Green Aluminum
- A Style (ARO) Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Allows matching of couplers for dedicated hose applications
- Easy to push to connect Air Compressor Accessories



Milton Industries ColorFit Coupler & Plug Kit (3 Piece), A-Style 1/4" NPT Green MIL S-303AKIT

- Durable and high scratch resistant Anodized Blue Aluminum
- T Style Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Allows matching of couplers for dedicated hose applications
- Easy to push to connect Air Compressor Accessories



Milton Industries ColorFit Coupler & Plug Kit (7 Piece), T-Style 1/4" NPT Blue MIL S-307TKIT

- Durable and high scratch resistant Anodized Blue Aluminum
- T Style Air coupler and plug fittings
- Steel sleeve provides superior durability, unlike traditional aluminum sleeves
- Allows matching of couplers for dedicated hose applications
- Easy to push to connect Air Compressor Accessories



Milton Industries ColorFit Coupler & Plug Kit (3 Piece), T-Style 1/4" NPT Blue MIL S-303TKIT

- Color-Coded (Black/Red) Durable Aluminum
- Contains one (1) Male Coupler, one (1) Female Coupler, two (2) Female Plugs and three (3) Male Plugs
- 1/4" I/M Industrial x 1/4" NPT



Tru-Flate® 7 Piece I/M Tru-Match Kit CPM 13-209R

- Color-Coded (Black/Red) Durable Aluminum
- Contains one (1) Female Coupler, one (1) Female Plug and one (1) Male Plug
- 1/4" I/M Industrial x 1/4" NPT



Tru-Flate® 3 Piece I/M Tru-Match Set CPM 13-207R

- Color-Coded (Green/Yellow) Durable Aluminum
- Contains one (1) Male Coupler, one (1) Female Coupler, two (2) Female Plugs and three (3) Male Plugs
- 1/4" A Aro x 1/4" NPT



Tru-Flate® 7 Piece A Tru-Match Kit CPM 13-309G

- Color-Coded (Green/Yellow) Durable Aluminum
- Contains one (1) Female Coupler, one (1) Female Plug and one (1) Male Plug
- 1/4" A Aro x 1/4" NPT



Tru-Flate® 3 Piece A Tru-Match Set CPM 13-307G

- Color-Coded (Orange/Blue) Durable Aluminum
- Contains one (1) Male Coupler, one (1) Female Coupler, two (2) Female Plugs and three (3) Male Plugs
- 1/4" T Automotive x 1/4" NPT



Tru-Flate® 7 Piece T Tru-Match Kit CPM 13-109B

- M-style coupler bodies are brass with brass sleeves.
- M-style plugs are case hardened steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 Degrees F.
- Air flow: 40 SCFM Kit includes (1) MIL715 1/4" NPT female coupler, (3) MIL727 1/4" NPT male plug and (1) MIL728 1/4" NPT female plug. Will interchange with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109.



Milton Industries 5 Piece 1/4" NPT M-Style Coupler and Plug Kit MIL S211

- A-style couplers are push type.
- A-style coupler bodies are steel, plated to resist rust.
- A-style plugs are case hardened steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI. Maximum temperature: 250 degrees F Kit includes: (1) #775 1/4" NPT female coupler; (1) #778 1/4" NPT female plug and (3) #777 1/4" NPT male plugs.



Milton Industries 5 Piece A-Style 1/4" Coupler and Plug Kit MIL S213

- M-style coupler bodies are brass with brass sleeves.
- M-style plugs are case hardened steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 degrees F Air flow: 40 SCFM
- Kit includes (1) #715 1/4" NPT female M-style coupler and (1) #727 1/4" NPT male M-style plug. Milton M-style "Kwik-change" couplers and plugs will interchange with all manufacturers who comply with the dimension requirements of military specification MIL-C-4109.



Milton Industries M-Style 1/4" Combination Coupler/Plug Kit MIL S711

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Greater airflow
- Air-tight seals
- Sleeve guard reduces risk of accidental disconnect
- Lasts longer



Tru-Flate® 1/4" I/M Coupler and Plug Set CPM 13-201

- 1/4" female national pipe thread coupler
- 1/4" Male national pipe thread plug
- Maximum inlet pressure of 300 pounds per square inch
- Buna-N seal
- 34 standard cubic feet per minute



Milton Industries 1/4" NPT A Style Coupler and Plug MIL S772

- T-style coupler bodies are brass. T-style plugs are case hardened steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 degrees F. Air flow: 40 SCFM
- Kit includes: (1) #785 1/4" NPT female T-style coupler and (1) #783 1/4" NPT male T-style plug.



Milton Industries 1/4" NPT T-Style Coupler/Plug Kit MIL S782

- Lightweight
- Lower cost than comparable product
- Push-to-connect design for one handed operation
- Unique valve design allows for greater air flow over standard couplers
- 3 year leak-proof guarantee



Tru-Flate® 1/4" MNPT Combo Coupler CPM 13-513

- The industry standard M style coupler
- Kwik Change couplers will interchange with all manufacturers
- 40 standard cubic feet per minute
- Maximum temperature of 250 degrees Fahrenheit

Image Shown: 715



Milton Industries 1/4" FNPT M Style Coupler MIL 715

Milton Industries 1/4" Female M Style Coupler MIL S-715

Milton Industries 3/8" FNPT M Style Coupler MIL 718

Milton Industries 3/8" FNPT M Style Coupler MIL S718

Milton Industries 1/4" FNPT M Style Push Type Coupler MIL S755

Milton Industries 1/4" FNPT M Style Coupler Drag Guard MIL 713

- M-style coupler bodies are brass with brass sleeves.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 degrees F
- Milton M-style "Kwik-change" plugs will interchange with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109.

Image Shown: S716



Milton Industries 1/4" NPT Male M-Style Coupler MIL S716

Milton Industries 3/8" MNPT M Style Coupler MIL 719

Image Shown: S790



Milton Industries 1/4" Female L Style Coupler 1 Pack MIL S790

Milton Industries 1/4" MNPT L Style Coupler MIL 794

- Lightweight/Compact design
- Lasts 3 times longer than standard couplers
- Push-to-connect design for one handed operation
- Unique valve design allows for greater air flow over standard couplers
- Lower cost than comparable product
- 3 year leak-proof guarantee



Tru-Flate® 1/4" FNPT Combo Coupler CPM 13-515

Milton Industries 1/4" Female A Style Coupler MIL S775

Milton Industries 1/4" NPT Male A-Style Coupler MIL S776

Milton Industries 1/4" NPT Male Plug A Style MIL S777

Milton Industries 1/4" NPT Female A-Style Plug - 2 Pack MIL S778

Image Shown: S775



- 1/4" female national pipe thread
- Air flow of 42 standard cubic feet per minute
- Made of heavy duty rust resistant brass
- Maximum of 300 pounds per square inch
- Buna-N seal

Image Shown: S-745




FTE 1/4" FNPT AMT Style Coupler MIL S-745

Milton Industries 1/4" MNPT AMT Style Coupler MIL S-746

- T-style coupler bodies are brass.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 degrees F.
- Air flow: 40 SCFM.

Image Shown: S785




Milton Industries 1/4" NPT Female Tru-Flate/Parker T Style Coupler 1 Pack MIL S785

Milton Industries 3/8" FNPT T Style Coupler MIL 788

Milton Industries 1/4" NPT Male Tru-Flate/Parker T Style Coupler 1 Pack MIL S786

- 1/4" female national pipe threads
- Maximum inlet pressure of 300 pounds per square inch
- Air flow of 74 standard cubic feet per minute
- Maximum temperature of 250°F

Image Shown: S-764



Milton Industries 1/4" FNPT V Style High Flow Coupler MIL S-764

Milton Industries 1/4" FNPT V Style High Flow Plug MIL S-761

Milton Industries 1/4" MNPT V Style High Flow Plug MIL S-760

Image Shown: S1833

Milton Industries 1/4" NPT Female Coupler Body MIL S1833

Milton Industries 1/4" MNPT H Style Coupler MIL 1834

Milton Industries 3/8" MLE BDY "H" MIL S1836

Milton Industries 1/4" NPT Male Plug H Style MIL S1839

Milton Industries 3/8" FNPT H Style Plug MIL S1838



Image Shown: S1803

- P-Style coupler 3/8 bodies are heavy duty steel.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250°F.
- Air flow: 68 SCFM



Milton Industries 3/8" P-Style 1/4" NPT Female Coupler MIL S1803

Milton Industries 1/4" MNPT P Style Coupler MIL 1804

Milton Industries 3/8" NPT Female P-Style Coupler MIL S1805

Milton Industries 3/8" MNPT P Style Coupler MIL S1806

Milton Industries 3/8" Male P-Style 1/4" NPT Coupler MIL S1809

Milton Industries 1/4" Female Plug MIL S1810

Milton Industries 3/8" NPT Male P-Style Plug MIL S1807

Milton Industries 3/8" Female Plug MIL S1808

Milton Industries 1/2" MNPT G Style Plug MIL 1857

Milton Industries 1/2" NPT Male G-Style Plug MIL S1817

Milton Industries 1/2" FNPT G Style Plug MIL 1858

Milton Industries 1/2" NPT Female G-Style Plug MIL S1818

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Maximum inlet pressure of 300 pounds per square inch
- Air flow of 99 standard cubic feet per minute
- Maximum temperature of 250°F
- G-Style coupler 1/2 bodies are heavy duty steel.

Image Shown: 1813



Milton Industries 3/8" FNPT G Style Coupler MIL 1813

Milton Industries 3/8" MNPT G Style Coupler MIL 1814

Milton Industries 1/2" NPT Female G-Style Coupler MIL S1815

Milton Industries 1/2" Male G-Style 1/2" NPT Coupler MIL S1816

Milton Industries 3/8" MNPT G Style Plug MIL 1819

Milton Industries 1/4" MNPT G Style Plug MIL 1855

- 3/8" female national pipe thread
- Maximum working pressure of 2,700 pounds per square inch
- Not to be used on hydraulic applications



Milton Industries 3/8" FNPT High Pressure Straight Through Coupler MIL 1765

- Maximum inlet pressure of 300 pounds per square inch
- Air flow of 40 standard cubic feet per minute
- Maximum recommended temperature of 250 degrees Fahrenheit



Milton Industries 3/8" Hose Barb M Style Coupler MIL 717-6

- M-style plugs are case hardened steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 degrees F
- Milton M-style "Kwik-change" plugs will interchange with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109.



Milton Industries 1/4" NPT Female M Style Plug MIL S728

- Longer life
- Better sealing
- Rust/Corrosion resistant

Image Shown: 12-135-2



Tru-Flate® 1/4" T x 1/4" FNPT Plug, 2 Pack CPM 12-135-2

Tru-Flate® 1/4" I/M x 1/4" FNPT Plug, 2 Pack CPM 12-235-2

Tru-Flate® 1/4" A x 1/4" FNPT Plug, 2 Pack CPM 12-335-2

Milton Industries 1/4" NPT Female Plug T Style MIL S784

Milton Industries 1/4" Male Tru-Flate/Parker T Style Plug - 2 Pack MIL S783

Image Shown: S784



- Longer life
- Better sealing
- Rust/Corrosion resistant

Image Shown: 12-125-2



Tru-Flate® 1/4" T x 1/4" MNPT Plug, 2 Pack CPM 12-125-2

Tru-Flate® 1/4" I/M x 1/4" MNPT Plug, 2 Pack CPM 12-225-2

Tru-Flate® 1/4" A x 1/4" MNPT Plug, 2 Pack CPM 12-325-2

Tru-Flate® 3/8" T x 1/4" MNPT Plug, 2 Pack CPM 12-603-2

- M-style plugs are case hardened steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI.
- Maximum temperature: 250 degrees F
- Milton M-style "Kwik-change" plugs will interchange with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109.

Image Shown: S727



Milton Industries 1/4" NPT Male M-Style Plug, 2 Pack MIL S727

Milton Industries 3/8" MNPT M Style Plug MIL S733

- L-Style couplers are push type.
- L-style couplers are steel, plated to resist rust.
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250 degrees F
- Air flow: 32 SCFM L-style Lincoln Interchange Series basic size.

Image Shown: S791



Milton Industries 1/4" NPT Male L Style Coupler 2 Pack MIL S791

Milton Industries 1/4" NPT Female L-Style Coupler 2 Pack MIL S792

- 1/4" Female national pipe thread
- Maximum inlet pressure of 150 pounds per square inch
- Air flow of 40 standard cubic feet per minute

Milton Industries 1/4" NPT Swivel Hose Fitting Connector with Flow Control MIL S-657-2



- Maximum inlet pressure of 150 pounds per square inch
- Controlled air flow up to 40 standard cubic feet per minute
- Built in gauge
- 1/4" Female national pipe thread

Milton Industries 3/8" NPT Swivel Hose Fitting Connector MIL S-657-1



- 1/4" male and female national pipe thread
- L shaped swivel adapter
- Can be used at the end of an air hose to prevent kinking during use

Milton Industries 1/4" NPT L Swivel Adapter MIL 660



- 1/4" Female national pipe thread
- Maximum inlet pressure of 150 pounds per square inch
- Air flow 40 standard cubic feet per minute

Milton Industries 1/4" NPT Swivel Hose Fitting Connector MIL S-657



AIR/POWER TOOLS & ACCESSORIES

AIR IMPACT WRENCHES

- 925 ft. lbs. of breakaway torque
- Maximum Torque 650 ft.-lbs. helps to break free fasteners that are stubborn or stuck
- 7500 RPM (Free Speed @ 90 PSI) helps provide high power fastening
- One Hand Operation-Forward/Reverse Switch for quick and easy switching
- Shock Resistant Housing Bumpers helps protect housing and prevent scuffing

DeWalt Tools 1/2" Drive Impact Wrench Heavy Duty SBD DWMT70773L



- 850 ft. lbs. of breakaway torque
- 600 ft.-lbs. of torque
- Heavy duty twin hammer mechanism
- Composite body design with shock resistant housing bumpers and ergonomic handle
- Adjustable power regulator

DeWalt Tools 1/2" Drive Impact Wrench Medium Duty SBD DWMT70774



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Powerful at 305 ft-lbs. of maximum torque in reverse
- Lightweight at only 2.9 pounds
- Steel front cover and aluminum body
- One hand operation forward/reverse by either left or right-handed users
- Three power setting positions

Chicago Pneumatic 3/8" Stubby Impact Wrench
CTO CP7731



- Ideal for overall automotive service, body shop, farm, and general automotive use.
- Durable swinging weight clutch mechanism.

ProValue 1/2" Impact Wrench EQP 2374PV



- This super-duty model is an advanced composite constructed impact wrench.
- Its weight to power ratio is unequalled in the world today.
- It is not only light-weight, evenly balanced, compact, ergonomically designed for unequalled comfort and strength; but also is the most powerful 1/2" impact wrench offered in the market.
- The advanced motor design, combined with the fast acting pin clutch, yields an output of 1,000 ft-lbs. in reverse.
- It features a three (3) way adjustable power selector, which provides the operator his desired working torque. Recommended for all applications, except tire assembly and shock absorber installation.

CARQUEST 1/2" Super-Duty Composite Impact Wrench, Pin Clutch EQP 7438



- "The Tire Tool!" Has all the features of the 7439 Twin Hammer Double Blow impact wrench including the advanced composite construction.
- However, this tool offers a 2" extended anvil for use with flip sockets.
- It is designed for the tire shops for assembly and disassembly of automobile tires.
- Its unmatched weight to power ratio for a twin hammer tool, gives the operator a light-weight tool with unequalled power to handle the toughest lugs.

CARQUEST 1/2" Super Heavy-Duty Composite Impact Wrench with 2" Anvil EQP 7440



- Powerful at 450 ft-lbs. of maximum torque in reverse
- Lightweight at only 2.9 pounds
- Steel front cover and aluminum body
- One hand operation forward/reverse by either left or right-handed users
- Three power setting positions

Chicago Pneumatic 1/2" Stubby Impact Wrench
CTO CP7732



- Powerful at 425 ft-lbs. of maximum torque in reverse
- DYNA-PACT (Pin clutch) with oil bath
- One-handed reverse button with 4 positive power settings
- Compact and ergonomic with rubber grip
- Through handle air exhaust
- This tool is part of the Chicago Pneumatic Classic Line

Chicago Pneumatic 1/2" Impact Wrench CTO CP734H



- Powerful at 610 ft-lbs. of maximum torque in reverse
- Built with Chicago Pneumatic's patented Spring Hammer Double dog-oil bath clutch
- One-handed reverse button with 4-power settings
- Compact design with comfortable contoured handle
- This tool is part of the Chicago Pneumatic Classic Line

Chicago Pneumatic 1/2" Impact Wrench CTO CP749



- Model Number: CP7748
- Powerful - producing 960 ft. lbs. of max torque in reverse
- New - One-handed forward & reverse system (Ring system)
- Durable - Hard anodized end plates / Hard chromium aluminum cylinder / Twin hammer mechanism
- Lightweight - 4.4 lbs. thanks to its composite motor housing
- Compact - at only 6.89" in length
- Comfortable - Curved handle with rubber material resistant to most chemicals used in workshops
- Great control - full teasing trigger

Chicago Pneumatic 1/2" Impact Wrench CTO 8941077481



- High power with 955 ft-lbs. of maximum real torque in reverse
- Weight of the tool is 3.95 pounds
- This tool is 6.7 inches in length
- Aluminum alloy front housing
- Composite housing

Chicago Pneumatic 1/2" Impact Wrench
CTO CP7749



- Access: There is no place for work to hide; as this compact design gives the user the admittance and power they need, even if the task is up, under, over, or around any awaiting obstruction
- Reliability: Built on the IR Impactool legacy, this tool is testing at 2x the life of competitive products available today. This tool will be the most reliable for an extensive period of time, no matter the application.
- Power-To-Weight: At 2.4 pounds, this tool is the lightest on the market, and it still manages to produce a torque output that can compete with the best; making it a power-to-weight leader in its class.
- Control: With the forward/reverse buttons located on the back of the tool, one-handed governance has never been this convenient. It features 3 different regulation settings (in forward) on its easy to operate power regulator dial.

Ingersoll Rand 1/2" Ultra-Compact Impactool IR 35MAX



- Power: Punish the toughest bolts with 780 ft-lbs of max reverse torque and 1,100 ft-lbs of nut-busting torque powered by Ingersoll Rand's finely tuned motor and twin-hammer mechanism
- Weight: Only 4 lbs. so your hand tires less, letting you get more work done
- Sound Reduction: Ingersoll Rand's Quiet Technology reduces the sound of the tool sparing your ears without sacrificing power
- Reliability: Rigorously tested, every component, mechanism and function of the 2135QXPA has been pushed to the limits to ensure it always performs in the face of the toughest jobs

Ingersoll Rand 1/2" Impactool IR 2135QXPA



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Power: Punish the toughest bolts with 1,350 ft-lbs of nut busting torque powered by Ingersoll Rand's finely tuned twin-hammer impact mechanism.
- Comfort: At only 4.6 pounds, the 2235 Series Titanium Impact Wrench can not be matched for power and weight in the market. With less weighing you down, you can work harder and faster for longer stretches of time.



- Reliability: Every component, every mechanism and every function of the 2235 Series has been put through the most rigorous testing to ensure it always performs in the face of the toughest applications. The 2235 Series is a finely tuned workhorse.
- Durability: Born from the legendary durability of the Ingersoll Rand 2135 Series, the 2235 pushes toughness to the next level. It's built with a titanium hammercase, steel-wareplate and strong composite housing that protects the tool from the harshest environments.

Ingersoll Rand 1/2" Impactool IR 2235TIMAX

- Adjustable power regulator
- Pressure-fed lubrication
- Easy-to-service 2-piece construction



Ingersoll Rand 1/2" Air Impactool IR 231C

- Pressure-fed lubrication system
- Handle exhaust directs air away from user
- Adjustable power regulator



Ingersoll Rand 1/2" Air Impactool IR 231HA

- High power with 1,200 ft-lbs. of maximum real torque in reverse
- Twin hammer high performance clutch
- Combined power regulator with forward/reverse
- Ergonomic handle exhaust keeps air away from the operator



Chicago Pneumatic 3/4" Impact Wrench CTO CP7763

- Model Number: CP7769
- Powerful - producing 1,440 ft. lbs. of max torque in reverse
- Lightweight - 6.9 lbs. thanks to its composite motor housing
- Compact - at only 7.9" in length
- High Durability - Twin hammer mechanism
- Ergonomic - All controls within reach, variable speed trigger, one-handed power & forward/reverse adjustment system
- More Secured - Socket retainer ring combined with hole retainer



Chicago Pneumatic 3/4" Impact Wrench CTO 8941077691

- Powerful at 1,000 ft-lbs. of maximum torque in reverse
- DYNA-PACT oil bath clutch
- Single handed reverse button with 4 power settings
- Comfortable handle grip
- 360 degree air inlet swivel
- This tool is part of the Chicago Pneumatic Classic Line



Chicago Pneumatic 3/4" Impact Wrench CTO CP772H

- Smaller and up to 2 lbs. lighter than other 3/4 inch impacts in its class
- Rocking dog impact mechanism works well on a wide range of air pressures
- Silenced exhaust reduces tool noise while in use



Ingersoll Rand 3/4" Air Impactool IR 259

- Jumbo hammer mechanism
- Up to 1,100 ft-lbs. of torque
- Pressure-fed lube system for trouble-free performance and longer life



Ingersoll Rand 3/4" Air Impactool IR 261

- MAX Power: 1350 ft-lbs maximum reverse torque from a tool that weighs just 7.4 lbs and is compact enough to access tight spaces
- MAX Durability: Built to last and designed to withstand tough use in rugged environments
- MAX Productivity: An air motor that's 16% more efficient than its predecessor and an easy-to-clean inlet screen means less downtime, better performance, and less money spent on compressed air



Ingersoll Rand 3/4" Quiet Impact Wrench IR 2145QIMAX

- Powerful at 1,770 ft-lbs. of maximum torque in reverse
- Pinless closed reinforced rocking dog clutch mechanism
- Thermo Plastic Rubber handle and side handle that is able to rotate in 4 positions
- Regulator integrated in forward/reverse knob with 3 power setting positions in both directions
- Tool includes a rubber bumper that protects both the application and the tool



Chicago Pneumatic 1" Impact Wrench CTO CP7776

- High power with 1,920 ft-lbs. of maximum real torque in reverse
- D-Handle Impact Wrench with dual retainer
- Pinless closed reinforced rocking dog impact mechanism
- Ergonomic side handle
- Integrated protective cover on the clutch housing



Chicago Pneumatic 1" Impact Wrench CTO CP7782

- Delivers 1,770 ft-lbs. maximum torque
- Fast-torque delivers 1,000 ft-lbs. in 2 seconds
- Improved feather touch trigger



Ingersoll Rand 1" Extended Anvil Air Impactool IR 285B6

AIR/POWER TOOLS & ACCESSORIES

AIR RATCHETS

- Ergonomic Handle with rubber cushion grip for comfort
- Maximum Torque 65 ft.-lbs. helps free stubborn bolts
- Touch Control Trigger allows user to apply needed amount of power

Dewalt Tools 3/8" Drive Air Ratchet SBD DWMT70776L



- 25 ft.-lbs. max torque
- Low profile forward/reverse control
- Head construction offers increased durability
- Ergonomic design

Ingersoll Rand 1/4" Air Ratchet Wrench IR 105-D2



- Ergonomic square handle design for positive comfort grip.
- Teasing throttle for precise speed control.
- Efficient 1/2 HP motor is ideal for exhaust systems, small engines, water pumps, fuel pumps, radiators, etc.

ProValue 3/8" Air Ratchet Wrench EQP 2328PV



- Compact head design for easy access to tight work spaces
- Hardened gears

Chicago Pneumatic 3/8" Ratchet Wrench CTO CP886



- 54 ft.-lbs. maximum torque
- 360 degree adjustable exhaust directs air away from the operator and the work
- Variable speed lever-style throttle

Ingersoll Rand 3/8" Air Ratchet Wrench IR 107XPA




AIR/POWER TOOLS & ACCESSORIES

AIR DRILLS

- Powerful 0.5 HP (375 W) energy efficient motor resists stalls
- Triple idler planetary gearing for smooth operation and extended tool life
- Handle exhaust reduces noise and directs air away from work area
- This tool is part of the Chicago Pneumatic Classic Line

Chicago Pneumatic 3/8" Drill CTO CP785



- Reversible motor with convenient control
- High quality Jacobs chuck
- Rear exhaust
- Grease point on angle head for easy maintenance

Ingersoll Rand 3/8" Chuck Right Angle Drill IR 7807R



AIR/POWER TOOLS & ACCESSORIES

CHUCK KEY

- Has 4 sizes.
- Strong neodymium magnets for attachment close to the worksite or toolbox.
- Cast alloy steel for strength.

Lisle Small Master Chuck Key LST 12050



AIR/POWER TOOLS & ACCESSORIES

AIR GRINDERS

- 25000 RPMs for fast material removal
- Cushion grip body provides maximum comfort
- Self-locking touch control trigger prevents accidental start ups when not in use

Dewalt Tools Straight Die Grinder SBD DWMT70783



- Standard safety lever.
- Variable speed throttle control.
- Full ball bearing construction, with built-in regulator.
- Ideal for high speed blending, smoothing, porting and deburring in confined areas.

ProValue 1/4" Rear Exhaust Die Grinder EQP 2320PV



- The 22,000 rpm motor provides a high material removal rate
- Powerful 0.6 HP (470 W) motor
- General maintenance applications
- Productivity and control
- Ideal for moldings and general high-speed polishing and grinding
- Robust aluminum alloy body
- CP streamline safety lever
- Built-in air regulator
- Includes 1/4" and 6 mm collets

Chicago Pneumatic 1/4" Die Grinder CTO CP872



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Powerful 0.32 HP (240 W) motor
- Low noise level at only 81 dB(A)
- 28,000 rpm free speed
- Rear exhaust
- Rubber overmould grip



Chicago Pneumatic 1/4" Die Grinder CTO CP9105Q-B

- Powerful 0.32 HP (240 W) motor
- Low noise level at only 81 dB(A)
- 27,000 rpm free speed
- Rear exhaust
- Rubber overmould grip



Chicago Pneumatic 1/4" Extended Die Grinder CTO CP9110Q-B

- Powerful Motor delivers 0.25 HP (0.19 kW) at 28,000 rpm free speed
- Durable Ball-bearing Construction improves balance, reduces vibration, and ensures a longer life
- Strong Aluminum Housing withstands tough operating conditions access to tight spots
- Safety-Lock Throttle Lever is easy to use and can prevent accidental start up
- Front Exhaust helps keep work surface clean



Ingersoll Rand Straight Die Grinder IR 307B

- Powerful motor delivers 0.33 HP (0.25 kW) and 25,000 rpm free speed
- Lightweight, durable, ergonomic composite housing protects tool from cold air and offers greater operator comfort
- Integral safety-lock throttle lever prevents accidental start up
- Rear exhaust directs air away from the operator



Ingersoll Rand Straight Air Die Grinder IR 308B

- 20000 RPM (Free Speed @ 90 PSI) for heavy duty applications
- Rear Air Exhaust helps blow exhaust away from work surface
- Touch Control Trigger allows user to apply needed amount of power



Dewalt Tools Angle Die Grinder SBD DWM70782L

- 83° offset angle.
- Ergonomically designed gearless motor (the motor is in the head, not the handle).
- Collet is 1/4" capacity, but tool accepts 1/4", 3 mm and 6 mm.
- Drop-in motor, hardened steel cylinder maximizes air utilization, rear exhaust and enhanced muffler system.
- Lightweight composite housing reduces vibration and is thermal-insulated to prevent hot or cold air transmission to operator. Rear exhaust over hose further reduces noise levels by as much as 8 dB. Eliminates exhaust from operator/work piece. 3-3/4" low profile provides greater operator control to access hard-to-reach areas. Gearless motor decreases downtime and lessens repair expense when compared to geared tools.



CARQUEST 1/4" Gearless Angle Die Grinder EQP 7446

- Compact, lightweight design for easy maneuverability
- 90 degree angle head allows flexibility in tight quarters
- 1/4" and 6 mm collets
- Built-in air regulator



Chicago Pneumatic 1/4" Mini 90° Angle Die Grinder CTO CP875

- Powerful 0.32 HP (240 W) motor
- Low noise level at only 81 dB(A)
- 23,000 rpm free speed
- Rear exhaust
- Rubber overmould grip



Chicago Pneumatic 1/4" 90° Angle Die Grinder CTO CP9106Q-B

- Powerful 0.32 HP (240 W) motor
- Low noise level at only 81 dB(A)
- 23,000 rpm free speed
- Rear exhaust
- Rubber overmould grip



Chicago Pneumatic 1/4" 120° Angle Die Grinder CTO CP9108Q-B

- Powerful motor delivers 0.25 HP (0.19 kW) and 21,000 rpm free speed
- Durable ball-bearing construction improves balance, reduces vibration, and ensures a longer life
- Strong aluminum housing withstands tough operating conditions
- Small and lightweight design provides easy operation and greater access to tight spots



Ingersoll Rand Angle Air Die Grinder IR 301B

AIR/POWER TOOLS & ACCESSORIES

AIR CUTTERS

- Rugged, energy efficient 0.5 HP (370 W) motor
- Heavy-duty high speed cutter
- Lightweight tool at 1.63 pounds
- Square handle design for positive grip
- Lock-off lever to prevent accidental start-up




Chicago Pneumatic Cut-off Tool CTO CP861

- Large hooked locking throttle lever provides user comfort and safety
- Steel shield deflects debris away from operator
- Front exhaust



Ingersoll Rand EDGE Series Air Cut-Off Tool IR 326

- Includes five (5) 3" x 1/16" thick disks with arbor hole
- Rated to 25,000 RPM
- Can be used for cutting through metal, fiberglass, plastic, and steel piping.



Tru-Flate® Air Tool Cut-Off Discs, 5 Pack CPM 25-311

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

AIR/POWER TOOLS & ACCESSORIES

AIR SAWS

- Great power and speed of 10,000 strokes per minute
- 3/8" stroke length
- Very low vibration
- 360 degree swivel air inlet



Chicago Pneumatic Air Saw CTO CP7901

AIR/POWER TOOLS & ACCESSORIES

AIR HAMMER

- Powerful at 7.2 joule
- Heavy duty pistol grip hammer
- Standard .401 round shank
- The internal muffler minimizes exhaust sound
- Unique vibration damping

Chicago Pneumatic Air Hammer Kit
CTO CP7110K



- Most powerful hammer in its class at 9.5 joule
- Standard .401 round shank
- Longer piston stroke for more power
- Kit includes: flat chisel, tapered punch, spot weld splitter, single blade panel cutter, edging chisel, quick change retainer and oiler

Chicago Pneumatic Air Hammer Kit
CTO CP7150K



- Up to 3,000 blows per minute
- Alloyed steel barrel and heat-treated piston for longer life
- Built-in power regulator and trigger control
- Kit Includes: 6 Chisels (3/4" flat blade, punch, claw ripper-edging tool, single blade cutter, kwik cutter, and a vee chisel-spot welder breaker), and carrying case

Ingersoll Rand Super Duty Air Hammer Kit
IR 121-K6




- MAX Comfort: Anti-vibration feature reduces tool vibration by over 30% when compared to standard air hammers
- MAX Power: 15% increase in impact force over standard air hammer product offering
- MAX Productivity: Quick-change retainer allows for faster chisel changeovers, so you can get the job done
- Kit Includes: 122MAX Air Hammer, Quick change retainer, 5-piece chisel set & case

Ingersoll Rand Short Barrel Air Hammer Kit
IR 122MAXX



- The Air Chisel Hammer features a medium barrel design with shock resistant housing bumpers and ergonomic handle.
- At 2600 beats per min., the tool is ideal for automotive applications such as ball joint removal and panel cutting for body work.
- Comes with full set of chisels

Dewalt Tools Chisel Hammer SBD DWMT07085



- Hardened alloy steel barrel.
- Standard .401" shank size.
- Accepts all standard .401" shank toolbits.
- Independent power regulator and teasing trigger for operator control.
- Ideal for muffler and pipe removal, body shop work, shock work, scraping rust and light front-end work.

ProValue Heavy-Duty Air Hammer EQP 2375PV



- The most commonly used 7" chisels all in one set.
- Fits all air hammers with .401" shank.

ProValue Heat Treated Chisel Set
EQP 2550PV

ProValue Chisel, Panel Cutter
EQP 2555PV

ProValue Chisel, Flat 3/4" Blade
EQP 2556PV

ProValue Chisel, Tapered Punch
EQP 2557PV

ProValue Chisel, Straight Punch
EQP 2558PV

ProValue Chisel, Claw Ripper EQP 2559PV



Image Shown: 2550PV

- Can be used for ripping sheet metal, cutting through bolts, screws, and nails
- Made from heat-treated steel alloy for more strength and longer life

Tru-Flate® Air Tool Chisel Set, 4 Pack CPM 25-310



- Used for easy changing of all chisels.
- Fits all standard .401" shank air hammers

ProValue Bee Hive Quick Change Retainer EQP 2500PV



AIR/POWER TOOLS & ACCESSORIES

AIR SCALER

- 4600 blows per minute
- Each needle 3.2 mm
- 19 needles included

Ingersoll Rand Standard Duty Needle Scaler IR 125



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

AIR/POWER TOOLS & ACCESSORIES

AIR SANDERS

- Sander has 2" and 3" Hook and Loop pads
- Rubber molded pistol grip
- Adjustable power regulator
- Progressive throttle
- Muffled handle exhaust

Chicago Pneumatic Mini Random Orbital Sander Kit CTO CP7200-S



- This is a general duty sander with rotary or random orbital options
- Uses a PSA sanding pad
- Has an insulated grip
- The lock off throttle can prevent accidental start-ups
- 10,000 rpm free speed

Chicago Pneumatic Dual Action Sander CTO CP870



- Low vibration
- Balanced ball bearing construction
- Adjustable built-in regulator for positive speed control

Ingersoll Rand Dual-Action Quiet Air Sander 6" Pad IR 311A



- Orbital motion.
- All new cross bolt-style hub mounting.
- All steel balance minimizes vibration while blending and smoothing filler, feather edging and pre-paint preparation.
- 6" sander.
- Includes sanding pad.

ProValue Dual Action Quiet Air Sander EQP 2310PV



- One-piece vinyl bonded (no rivets) pad.
- Used for all dual-action sanders.
- The 6", "flex" pad is ideal for sanding and feathering painted surfaces.

ProValue Dual Action Sanding Pad EQP 2527PV



- Contains three (3) 40-grit and three (3) 60-grit sanding disks, one (1) fine finish and one (1) medium finish prep pad, one (1) back-up pad and one (1) 1/4" mandrel

Tru-Flate® Air Tool Sanding Prep Kit, 10 Pack CPM 25-319



- Palm Sander has a 3/16" orbit
- Powerful 0.3 HP (210 W) motor
- Soft grip, tear drop design for perfect control
- Low noise level
- Shut-off speed control switch

Chicago Pneumatic 6" Orbital Sander CTO CP7255



- Composite Body Design provides durability and lightweight design
- 12000 RPM (Free Speed @ 90 PSI) for professional quality sanding
- Stick-On Pad for quick and easy changeover
- Touch Control Trigger allows user to apply needed amount of power

Dewalt Tools Palm Sander SBD DWMT70781L



- This dual piston in-line sander features a four (4) cylinder driving system of opposed, double-acting pistons.
- It is also capable of more than 3,300 one-inch strokes per minute.
- Because the dual pistons are constantly working in alternate opposition to one another, there is no dead center.
- This gives it unparalleled power on the job and fatigue proof smoothness.

CARQUEST Dual Piston In-Line Sander EQP 7474



- Powerful, heavy-duty dual piston design
- Compact and lightweight at 6 pounds
- Easy comfort trigger and handle

Chicago Pneumatic In-line Sander CTO CP7268



AIR/POWER TOOLS & ACCESSORIES

AIR PAINT GUNS

- Gravity High Volume Low Pressure Design

Dewalt Tools Gravity Feed Spray Gun HVLP SBD DWMT70777



- The material savings with this HVLP is upwards of 30% due to high transfer efficiency and low over spray.
- Easy handling and easy maintenance, fluid nozzle is stainless steel, air cap and gun head are chrome plated brass.
- The gun outlet pressure is less than 10 psi with a high transfer efficiency of over 65%.
- Specially designed air passage provides a very fine and even particle distribution.

ProValue Professional HVLP Gravity Feed Spray Gun EQP 2304-PV



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Die Cast aluminum alloy gun with a 2-step trigger control, self-centering chrome-molybdenum steel nozzle, spray gun adjustment, viscosity adjustable, non-bleeder type, gravity feed and external mix makes this gun the choice of the professionals.

ProValue Gravity Feed Spray Gun EQP 2305PV



- Designed for light and medium material delivery to handle a full range of viscosity from fine surface finishes to heavy body coatings.
- Stainless steel fluid nozzle.
- Chrome plated brass end cap.
- Brass gun head. Brass adjustment tube.
- Fully adjustable spray pattern with a 1 quart spun aluminum, dripless siphon cup. Precisely machined, well balanced, light weight and longer serviceability. Non-bleeder type, siphonal feed. Die-cast aluminum alloy gun body with 2-step trigger control. Self-centering nozzle. Wide-mouth and non-drip canister with quick release clamp lid.

ProValue Spray Gun & Cup EQP 2307PV



- Self centering stainless steel nozzle, chrome plate end cap, brass gun head and adjustment tube makes this high pressure spray gun ideal for painting results required in fine automotive or industrial type finishing.
- The die-cast aluminum gun body with a 2-step trigger, 1 quart spun aluminum canister with a quick release clamp lid helps make the most difficult job easier.

ProValue High Pressure Professional Spray Gun EQP 2308PV



- A 20 oz. gravity feed spray gun cup replacement.
- Durable, lightweight nylon construction.
- Fits most gravity feed spray guns.

ProValue Nylon Paint Cup For Gravity Feed Spray Guns EQP 2623PV



- Highly effective in removing contaminants from paint.
- Fits most gravity feed spray guns.
- Use once and throw away.

ProValue Gravity Feed Spray Gun Filters EQP 2620PV



- Designed to clean paint residue and sludge from all spray guns, keeping them in maximum working condition.
- Safe to use with chemicals and solvents.
- Specifically designed for high volume low pressure (HVLP) guns.
- 12 pieces.

ProValue Spray Gun Cleaning Kit EQP 2621PV



- Filters trap moisture, rust, scale and oil aerosols that pass through conventional filters.
- Install at or close to the spray gun for the final filtration for perfectly clean air.
- Air inlet/outlet - 1/4" NPT.

ProValue Spray Gun In-Line Air Filters EQP 2640PV



AIR/POWER TOOLS & ACCESSORIES

AIR REGULATORS

- Compact/Lightweight
- Allows for easy "on the tool" air adjustment.
- Ideal for paint spray guns/other pneumatic tools
- Keeps air flow at exact operating pressures
- Great where precise air flow is desired

Tru-Flate® In-Line Air Regulator with Gauge CPM 41-135



- Has 1 precision tapered valve that will open and close in approximately 4 turns.
- The easy to handle knob makes the valve infinitely adjustable.
- The air inlet is 1/4" m.p.t and the outlet is 1/4" f.p.t (swivel nut).

ProValue Air Adjusting Valve with Gauge EQP 2642-PV



- High volume air adjusting valve designed especially for HVLP spray guns.
- Includes a pressure gauge that reads up to 160 psi.
- The air inlet is 1/4" NPTM and the outlet is 1/4" NPTF (swivel nut).
- Fits all leading spray guns.

ProValue High Volume Air Adjusting Valve with Gauge EQP 2643-PV



- Includes a pressure gauge that reads up to 160 psi and has a full diaphragm regulation for constant, exact pressure.
- The air inlet is 1/4" NPTM and the outlet is 1/4" NPTF (swivel nut).
- Fits all leading spray guns.

ProValue Air Adjusting Valve With Diaphragm EQP 2644-PV



- Has 1 precision tapered valve that will open and close in approximately 4 turns.
- The easy to handle knob makes the valve infinitely adjustable.
- The air inlet is 1/4" NPTM and the outlet is 1/4" NPTF (swivel nut).

ProValue Air Adjusting Valves EQP 2641-PV



AIR/POWER TOOLS & ACCESSORIES

AIR TOOL OIL

- Cleans & Restores Pneumatic Tools
- Reduces Friction
- Protects Tools from Freezing Down to -25°F

Blaster Professional Air Tool Conditioner , 11 oz. BLT 16-ATC



- Lubricate, increase efficiency, reduce wear, prevent carbon build up

Ingersoll Rand 1 Quart Bottle of All Season Select Lubricant Oil IR 38436739



- Working temperature of 5°F to 350°F
- International Standards organization velocity grade of 32
- 32 oz. flip top bottle
- Protects tools in storage
- Absorbs moisture

Milton Industries Air Tool Oil, 32 oz. MIL 1001-32



AIR/POWER TOOLS & ACCESSORIES

CORDLESS IMPACT WRENCHES

- Compact (5.70" front to back), lightweight (3.4 lbs.) design fits into tight areas
- Li-Ion batteries with fuel gauge provide 33% more capacity over standard packs
- Three (3) LED lights with 20 second delay after trigger release provides visibility without shadows
- Hog ring anvil to easily change sockets
- Textured anti-slip comfort grip provides maximum comfort and control



DeWalt Tools 20V MAX 3/8" Impact Wrench Kit SBD DCF883M2

- Compact (5.70" front to back), lightweight (3.4 lbs.) design fits into tight areas
- Three (3) LED lights with 20 second delay after trigger release, provide visibility without shadows
- Hog ring anvil to easily change sockets
- Textured anti-slip comfort grip provides maximum comfort and control
- Li-Ion batteries with fuel gauge provide 33% more capacity over standard packs



DeWalt Tools 20V MAX 1/2" Impact Wrench Kit SBD DCF880HM2

- The DCF889HM2 20V MAX* Lithium Ion 1/2" High Torque Impact Wrench Kit features a hog ring anvil for quick and easy change sockets
- Hog ring anvil for quick & easily change sockets

DeWalt Tools 20V MAX 1/2" High Torque Impact Wrench Kit SBD DCF889HM2



- Up to 700 ft.-lbs. of max torque and 1200 ft.-lbs. of max breakaway torque
- Compact design of 8-13/16" in length and weighs only 7.2 lbs.
- Multi-speed control for a variety of applications (0-400/ 1,200/ 1,900 RPM)
- 1/2" Anvil with hog ring (also available with detent pin)
- Bright LED light for visibility



DeWalt Tools 20V MAX XR High Torque 1/2" Impact Wrench w/Hog Ring Anvil Kit (5.0Ah) SBD DCF899HP2

- Compact, lightweight design fits into tight areas
- 3/8" Hog ring anvil for fast socket changing
- 3 LEDs with 20-second delay after trigger release, provide visibility without shadows
- 1150 in.-lbs. of torque power for tightening and loosening

DeWalt Tools 12V MAX* 3/8" Impact Wrench Kit SBD DCF813S2



- High torque motor delivers 1450 in.-lbs. of torque
- High performance motor (0-2,800 RPM, 0-3,100 BPM) for quick fastening applications
- Compact (6.9" long) and light weight (3.3 lbs.) allows tool to work in tight areas and minimizes user fatigue
- Quick release 1/4" hex head chuck for easy one-handed bit changes
- Includes (3) Impact Ready Socket Adapters (3/8"; 1/4"; 1/2")



Porter Cable Power Tools 20-Volt 1/4" Cordless Variable Speed Impact Driver with Socket Adapters SBD PCC641LAS

- 330 ft.-lbs. of torque for heavy applications
- 1,700 RPM for speed of application
- 1/2" Hog Ring for ease of socket change
- LED light for visibility in dark areas
- Lightweight and balanced at 6.0 lbs. with battery

Porter Cable Power Tools 20V 1/2" Cordless Impact Wrench SBD PCC740LA



- 2.1 lbs. - 1.0 Kg
- 460 ft.-lbs. - 625 Nm of maximum torque in reverse
- 4 1/4 in - 108 mm length
- Jumbo hammer mechanism
- Steel motor

Chicago Pneumatic 1/2" Stubby Impact Wrench CTO CP7732C



- 2.1 lbs. - 1.0 Kg
- 346 ft.-lbs. - 470 Nm of maximum torque in reverse
- 4 1/4" - 107 mm length
- Jumbo hammer mechanism
- Steel motor

Chicago Pneumatic 3/8" Stubby Impact Wrench CTO CP7731C



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- INCLUDES: (1) M12 FUEL 3/8" Stubby Impact Wrench (2554-20), (1) M12™ REDLITHIUM™ CP2.0 Battery (48-11-2420), (1) M12™ REDLITHIUM™ XC 4.0 Extended Capacity Battery Pack (48-11-2440), (1) M12™ Lithium-ion Battery Charger (48-59-2401), (1) Belt Clip, (1) Carrying Case
- Our M12 FUEL™ 3/8" Stubby Impact Wrench is the industry's most compact cordless impact wrench.
- At only 4.8" in length, it allows you to work in tighter spaces delivering the power to complete many of the most demanding tasks and increasing your productivity.
- The compact impact delivers high torque with our POWERSTATE™ brushless motor.
- The impact wrench delivers an industry leading 250 ft-lbs. of breakaway torque.

Milwaukee Tool M12 FUEL 3/8" Stubby Impact Wrench Kit
MLW 2554-22



AIR/POWER TOOLS & ACCESSORIES

CORDLESS RACHETS

Includes:

- (1) M12 FUEL 3/8" Ratchet
- (1) M12 2.0 REDLITHIUM Battery
- (1) M12 Charger
- (1) Protective Boot
- (1) 3/8" to 1/4" Adapter
- (1) Carrying Case

The Milwaukee M12 FUEL 3/8" Ratchet is the first cordless tool that provides both the torque and compact size to replace pneumatic Ratchets in the industry. With up to 55 ft-lbs of max torque and 200rpm's, this tool is the ideal fastening solution for automotive mechanics and maintenance and repair professionals who demand maximum performance and convenient portability. A low profile head and cordless design allows for our users to have more access in tight spaces than competitive units. With the industry leading FUEL technology, a reinforced mechanism and investment cast steel yoke housing, this ratchet can withstand daily jobsite wear and tear for years of reliable use. Eliminate the constant maintenance of pneumatic ratchets and the nuisance of the air hose in the shop with the M12 FUEL Ratchet, which delivers the maximum portability and productivity for the professional user.

Milwaukee Tool M12 3/8" Ratchet Kit MLW 2557-21



Includes:

- (1) M12 FUEL 1/4" Ratchet
- (1) M12 2.0 REDLITHIUM Battery
- (1) M12 Charger
- (1) Protective Boot
- (1) 1/4" to 3/8" Adapter
- (1) Carrying Case

- Most Powerful: Delivers Industry Leading Torque Output of Up To 40 Ft-Lbs
- Most Compact: Up To 20% Smaller Head Size
- Most Durable: Worlds 1st Brushless Ratchet Provides 2X Longer Motor Life
- 1st In Class Torque To Head Size Ratio
- Premium Metal Components For Longer Durability

Milwaukee Tool M12 1/4" Ratchet Kit MLW 2556-21



AIR/POWER TOOLS & ACCESSORIES

CORDLESS DRILL

Porter Cable Power Tools 20V Drill Driver Kit SBD PCC601LAP



- Compact, lightweight design fits into tight areas
- High speed transmission delivers two speeds (0-450 & 1,500 rpm) for a range of fastening and drilling applications
- Ergonomic handle delivers comfort and control
- High performance motor delivers 300 unit watts out (UWO) of power ability completing a wide range of applications
- 1/2" single sleeve ratcheting chuck provides tight bit gripping strength

DeWalt Tools 20V MAX* Lithium Ion Compact Drill/Driver Kit
SBD DCD771C2



- Compact, lightweight design fits into tight areas
- Ergonomic handle delivers comfort and control
- High-speed transmission delivers 2 speeds (0-600 & 0-2,000 rpm) for a range of fastening and drilling applications
- 1/2" ratcheting chuck provides superior bit gripping strength

DeWalt Tools 20V MAX* Lithium Ion Compact Drill/Driver Kit (1.5 Ah) SBD DCD780C2



AIR/POWER TOOLS & ACCESSORIES

CORDLESS COMBOS

- DCD710 12V MAX* 3/8" drill/driver features a two-speed transmission (0-400 / 0-1,500)
- DCF815 12V MAX* 1/4" impact driver features 3 LED lights to provide visibility without shadows

DeWalt Tools 12V MAX* Cordless Li-Ion Drill/Driver / Impact Driver Combo Kit SBD DCK211S2



- The DCK280C2 20V MAX* Lithium Ion Compact Drill/Driver / Impact Driver Combo Kit (1.5 Ah) features a two-speed transmission and LED lights for working in dark spaces
- DCD780 20V MAX 1/2" drill/driver features two-speed transmission (0-600 / 0-2,000)
- DCF885 20V MAX 1/4" impact driver features 3 LED lights with 20-second delay to provide visibility without shadows

DeWalt Tools 20V MAX Lithium Ion Compact Drill/Driver / Impact Driver Combo Kit (1.5 Ah) SBD DCK280C2



* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

- Drill/driver features high performance motor and delivers 0-350/0-1,500 RPMs. 1/2" keyless chuck, LED work light. Compact and lightweight.
- Reciprocating saw features high performance motor delivering 1" stroke length and 0-3,000 SPMs. Tool free blade release. Variable speed trigger and pivoting shoe. Compact and lightweight.



Porter Cable Power Tools 20V Max Drill & Reciprocating Saw Combo Kit SBD PCC603L2

Kit Includes:

- (1) 2852-20 3/8"; Mid-Torque Impact Wrench
- (1) 2767-20 1/2"; High-Torque Impact Wrench
- (2) M18 5.0 XC Batteries
- (1) M18/M12 Multi-Voltage Charger
- (1) Tool Bag



- Most Powerful 1/2" Impact Wrench - 1,000 Ft-Lbs Fastening & 1,400 Ft-Lbs Nut Busting Torque
- Most Powerful 3/8" Impact Wrench - 600 Ft-Lbs Nut-Busting Torque
- Most Compact High Torque In the Industry - Up To 0.7" Shorter Length Than the Competition
- Over 60% Longer 3/8" Anvil Life Than Cordless Competitor
- Redlink Plus Intelligence Prevents Damage To the Tool and Battery Due To Overloading Or Overheating

Milwaukee Tool M18 FUEL 2 Piece Auto Kit - 1/2" HTIW & 3/8" MTIW MLW 2993-22

Kit includes: 3/8" Stubby impact, 1/4" Hex impact, CP2.0 Battery, XC 4.0 Extended capacity battery and battery charger

- Greatest access in tight spaces at 4.9" in length
- 250 ft.-lbs. breakaway torque
- 4-Mode Drive control
- Auto-Shut Off mode reduces over fastening and increases productivity
- One of 90+ Tools on the M12 System



Milwaukee Tool M12 FUEL 2 Piece Auto Kit - 3/8" Impact Wrench & 1/4" Impact Driver MLW 2599-22

AIR/POWER TOOLS & ACCESSORIES

CORDLESS GRINDERS

- 8,000 rpm motor provides high-power for cutting and grinding applications
- Tool-free guard allows for quick and easy guard adjustments/positioning
- 2-position side handle offers greater control, comfort and versatility
- Power to Grind
- Quick-Change™ Wheel Release allows for tool-free wheel changes without the need for a wrench



Dewalt Tools 20V MAX* Lithium Ion Grinder Tool Kit SBD DCG412P2

- 13 Amp Equivalent Motor as Compared to a D28144 Corded Unit
- Kickback Brake engages when a pinch, stall, or bind-up event is sensed and the electronic brake engages with maximum force to quickly stop the wheel, reduce the movement of the grinder, and shut the grinder off.
- 9,000 RPM Speed allows the use of up to 6" wheels
- Brake engages when trigger is released, stopping speeds of 1.5 seconds with standard grinding wheel (4-1/2" x 1/4" Bonded abrasive wheel, non-hubbed)
- E-Clutch activates in less than a tenth of a second when a pinch/stall is detected, shutting down the motor.



Dewalt Tools FLEXVOLT™ 60V MAX* Grinder
1 Battery Kit SBD DCG414T1

AIR/POWER TOOLS & ACCESSORIES

CORDLESS LIGHTS

- 3 bright LEDs illuminate dark jobsite work areas
- 2 brightness settings with 500 and 250 Lumens provides flexibility for maximum light output or extended run-time
- 140-degree pivoting head provides versatility for lighting work surfaces
- Built-in telescoping and 360-degree rotating hook allows unit to hang from 2" materials and multiple locations
- Over-molded lens cover provides increased durability and a non-marring surface for the jobsite



Dewalt Tools 20V MAX* LED Hand Held Area Light SBD DCL050

- 3 bright LEDs illuminate dark jobsite work areas
- 1 bright Red LED to preserve night vision
- 2 brightness settings provide flexibility for maximum light output or extended run-time
- 90-degree pivoting head provides versatility for lighting work surfaces
- Distance - Can be seen up to 508 yards or 1,525 feet



Dewalt Tools 20V MAX* Jobsite LED Spotlight
SBD DCL043

- 4 LED Bulbs delivers 120 Lumens for working in dark conditions
- Pivoting head easily adjusts beam towards working area
- Contoured Overmolded Handle optimized for increased comfort
- 20V Max System - High performance cordless platform



Porter Cable Power Tools 20V MAX* Lithium Bare LED Flash Light SBD PCC700B

- INCLUDES: (1) M12™ Underhood Light (2125-20), (1) M12™ REDLITHIUM™ XC 4.0 Extended Capacity Battery Pack (48-11-2440), (1) M12™ Lithium-ion Battery Charger (48-59-2401)
- SHINES BRIGHTER. GRIPS STRONGER. PROTECTS LONGER. The M12™ Underhood Light delivers 1350 lumens of TRUEVIEW™ High Definition Output for full engine coverage and clarity.
- Milwaukee's FINISHGUARD™ hooks resist wear providing lasting protection against scratches to a vehicle's finish.
- With 2X more gripping surface, get more contact for better positioning when mounting underhood, undercarriage or elsewhere.
- Rotate, slide, remove and hang the light bar for added flexibility and versatility.



Milwaukee Tool M12™ Underhood Light MLW 2125-21XC

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

AIR/POWER TOOLS & ACCESSORIES

REPLACEMENT BATTERIES & CHARGERS

- Lightweight design and quick 30-minute charge time
- No memory and virtually no self-discharge for maximum productivity and less downtime

Dewalt Tools 20V MAX* Lithium Ion Compact Battery Pack (1.5 Ah) SBD DCB201



- Compact XR Lithium Ion pack provides up to 33% more capacity than standard 20V MAX* battery packs
- 3-LED fuel gauge system allows immediate feedback on state of charge
- No memory and virtually no self-discharge for maximum productivity and less downtime
- Lightweight design and quick 35-minute charge time

Dewalt Tools 20V MAX* Compact XR Lithium Ion Battery Pack SBD DCB203



- The Power of Corded with the Flexibility of cordless
- 4X The Runtime of DCB201 1.5Ah Battery
- 3X The Power of DC9096 18V Battery
- Tri-Platform compatibility with 20V MAX*, 60V MAX* and 120V MAX*
- Durable construction with single piece cell holder

Dewalt Tools Flexvolt 20/60V MAX* Battery Pack 6.0 AH Dual Pack SBD DCB606-2



- The Power of corded, The Freedom of cordless
- 4X runtime compared to DCB201 1.5Ah Battery Pack
- 3X Power compared to DC9096 18V Battery
- Tri-Platform Compatibility 20V MAX*, 60V MAX* and 120V MAX*
- LED State of Charge Display

Dewalt Tools 20V/60V MAX* Flexvolt 6.0 Ah Battery SBD DCB606



- 1.5 amp/hours for additional runtime on the jobsite
- High energy flow cells improves performance of tools
- No memory and minimal self discharge so battery is ready when you are

Porter Cable Power Tools 20V MAX* Lithium Ion Compact Battery SBD PCC680L



- 2 Amp charge rate for fast recharging
- Overload protection protects from damaging cells
- Part of the Porter Cable 20V Max system

Porter Cable Power Tools 20V MAX* Lithium Ion Charger SBD PCC692L



AIR/POWER TOOLS & ACCESSORIES

CORDED GRINDERS

- 7 Amp AC/DC, 12,000 rpm motor designed for faster material removal and higher overload protection
- One-Touch™ guard eliminates the need for a tool to adjust the guard location
- Hex wrench replaces spanner wrench - hex wrench is found in most tool boxes if lost
- Low profile, jam-pot gear case increases durability and allows tool to fit into tight spaces
- Quick-Change wheel release allows tool-free wheel removal without the need for a wrench



Dewalt Tools 4-1/2" Small Angle Grinder with One-Touch Guard SBD DWE4011

- 12,000 RPM for high speed material removal
- Durable 6.0 Amp motor powers through jobsite tasks
- Tool-free guard change provides fast and easy adjustments
- Cast metal gear case for increased durability
- Spindle lock feature allows for single wrench wheel change



Porter Cable Power Tools 6.0 Amp 4-1/2" Small Angle Grinder SBD PCE810

AIR/POWER TOOLS & ACCESSORIES

CORDED BUFFERS

- Powerful, 12 amp, all ball bearing construction for long life
- Electronic control maintains specified speed under load delivering desired finish results
- Conveniently located variable speed dial lets user set maximum speed from 0-600/3500 rpm for different materials and applications
- Variable speed trigger allows user to control speed from 0 to dialed maximum setting
- Heat-treated, precision-cut steel gears for smooth operation



Dewalt Tools 7"/9" Variable Speed Polisher SBD DWP849

- A variable speed polisher that is ideal for slow polishing with the power needed for clear coat finishes.
- A convenient speed dial that allows you to adjust your speed with your thumb while still operating the tool.
- The electronic speed control maintains the consistent speed while under load.
- The 7" rubber backing pad allows for the use of a bonnet (included) for polishing or sanding disc for sanding.



CARQUEST 7" Variable Speed Electric Polisher EQP 7452

* Disclaimer: Not all products listed in this catalog are stocked in all stores or DC locations. If not stocked, they are available via special order.

AIR/POWER TOOLS & ACCESSORIES

CORDED IMPACT WRENCH

- 7.5 Amp motor for heavy duty applications
- 450 ft-lbs of torque for installing & removing heavy fasteners
- 2,200 RPM & 2,700 BPM provide fast application speeds
- 1/2" Hog ring anvil for easy socket changes

Porter Cable Power Tools 7.5 Amp 1/2" Impact Wrench
SBD PCE211



AIR/POWER TOOLS & ACCESSORIES

CORDED SANDERS

- 3.0 Amp motor that spins the pad at 12,000 OPM
- Shorter height allows the user to get closer to work piece
- Separate counterweight design reduces vibration for improved comfort
- Rubber over-mold in all of the critical areas of the sander
- Improved dust-sealed switch to protect against dust ingestion for longer switch life

Dewalt Tools 5" Single Speed Random Orbit Sander w/Hook & Loop Pad
SBD DWE6421



AIR/POWER TOOLS & ACCESSORIES

CORDED HEAT GUNS

- LCD display allows user to adjust temperature within 50-degree increments
- Built-in overload protection shuts the heating element down and prevents burn up
- Built-in hang ring adds a convenient storage feature
- Cord protector keeps the cord from tearing away from the housing
- Built-in innovative kickstand support provides greater stability and prevents tip over

Dewalt Tools Heat Gun Kit with LCD Display
SBD D26960K



- 1500 watts deliver high heat and multiple fan settings
- 2 speed selector delivers high and low fan speed settings
- Variable temperature dial allows for easy adjustment of temperatures
- Integrated support stand allows the gun to sit upright for hands free use
- Integrated hanging hook is ideal for storage

Porter Cable Power Tools 1500 Watt Heat Gun
SBD PC1500HG

